


- NOTE:
 -DESIGN CODES
 IBC 2015
 ASCE 7-10
 ACI 318-11
 AISC 360-10
 AWS D1.3
 -WIND SPEED-115 MPH (MPH 3-SEC GUST)
 -EXPOSURE C
 -DESIGN LOADS DERIVED FROM THESE CODES AND FORCES (#, #)
 -AXIAL-1,300 LBS
 -SHEAR-1,235 LBS
 -OVERTURNING MOMENT-4,555 LB-FT
 -USE CONCRETE WITH A 3000PSI MINIMUM COMPRESSIVE STRENGTH (f'c).
 -PIER DEPTHS REQUIRED ARE MINIMUMS. ALL PIERS TO EXTEND TO FROST DEPTH AS DETERMINED BY LOCAL JURISDICTION.
 -TOP OF PIERS SHALL BE SLOPED SUCH THAT MOISTURE CANNOT ACCUMULATE.
 -ELECTRICAL CONTRACTOR TO PROVIDE INFORMATION ON CONDUIT AND ELECTRICAL REQUIREMENTS.
 -MINIMUM ALLOWABLE LATERAL SOIL BEARING PRESSURE 100 PSF/FT OF DEPTH (x2)
 -TOP 6" OF SOIL NEGLECTED IN EMBEDMENT DEPTH CALCULATIONS (EMBEDMENT DEPTHS SHOWN ARE FROM GRADE).
 -PROVIDE A MINIMUM OF 3" CONCRETE COVER FOR ALL EMBEDDED STEEL.
 -FOUNDATION IS DESIGNED FOR SINGLE OR DOUBLE POLE COLUMNS
 -ALL REINFORCING STEEL BY GENERAL CONTRACTOR.




(A) ORDER HERE CANOPY
 115 MPH
 NTS


- NOTES:
 -TOP OF PIERS SHALL BE SLOPED SUCH THAT MOISTURE CANNOT ACCUMULATE.
 -USE F1554 GRADE 36 BOLTS MINIMUM
 -USE HOT DIPPED GALVANIZED BOLTS
 -ANCHOR BOLTS TO BE SET IN ACCORDANCE WITH AISC CODE OF STANDARD PRACTICE
 -ANCHOR RODS, NUTS, AND WASHERS SHALL BE SHIPPED AS AN ASSEMBLY FROM THE SIGN/LIGHTING MANUFACTURER
 -DO NOT CUT ANCHOR BOLTS AFTER INSTALLATION OF POLE

FOUNDATION NOTE

ATTENTION CONTRACTOR:
 VERIFY ALL SIGN FOUNDATIONS
 REQUIRED WITH SIGN PROVIDER



- NOTES:
 -TOP OF PIERS SHALL BE SLOPED SUCH THAT MOISTURE CANNOT ACCUMULATE.
 -ANCHOR RODS, NUTS, AND WASHERS SHALL BE SHIPPED AS AN ASSEMBLY FROM THE SIGN/LIGHTING MANUFACTURER
 -DO NOT CUT ANCHOR BOLTS AFTER INSTALLATION OF POLE



(C) CONNECTION DETAILS
 NTS

GENERAL NOTES

- THE FOLLOWING CODES WERE USED IN DESIGN:
 -IBC 2015
 -ASCE 7-10
 -ACI 318-11
 -AISC 360-10
 -AWS D1.3
 -WIND SPEED 115 MPH, 3 SEC GUST
 -EXPOSURE C
 -DESIGN LOADS DERIVED FROM THESE CODES AND FORCES
 -AXIAL - 1,300 LBS
 -SHEAR - 1,235 LBS
 -MOMENT - 4,555 LB-FT
- ALL FOOTING EXCAVATIONS ARE TO BE CLEAR OF WATER AND FOREIGN MATTER BEFORE PLACING CONCRETE
 -MINIMUM ALLOWABLE LATERAL SOIL BEARING PRESSURE OF 100PSF/FT (x2)
 -SITE SOIL CONDITIONS TO BE CONFIRMED BY GEOTECHNICAL ENGINEER. IF ASSUMED SOIL CONDITIONS ARE NOT PRESENT, FOUNDATION SHALL BE DESIGNED BY A LICENSED STRUCTURAL ENGINEER TAKING INTO ACCOUNT ACTUAL SITE SOIL CONDITIONS.
 -TOP 6" OF SOIL NEGLECTED IN EMBEDMENT DEPTH CALCULATIONS (EMBEDMENT DEPTHS SHOWN ARE FROM GRADE)
- ELECTRICAL CONTRACTOR TO PROVIDE INFORMATION ON CONDUIT AND ELECTRICAL REQUIREMENTS.

CONCRETE:

- ALL FOOTINGS SHALL BEAR ON FIRM UNDISTURBED RESIDUAL SOIL AND/OR ENGINEERED EARTH FILL COMPACTED TO 98% OF ITS MAXIMUM DRY DENSITY AS PER ASTM D 698-70 (STANDARD PROCTOR) UNLESS NOTED OTHERWISE.
 -ALL PIERS TO EXTEND TO FROST DEPTH AS DETERMINED BY LOCAL JURISDICTION.
 -TOP OF PIERS SHALL BE SLOPED SUCH THAT MOISTURE CANNOT ACCUMULATE.
 -MINIMUM CONCRETE STRENGTH (f'c) SHOULD CONFORM WITH MCDONALDS CAST-IN-PLACE CONCRETE SPECIFICATIONS SECTION 2.13-A
 -USE OF ADMIXTURES SHALL CONFORM TO MCDONALDS CAST-IN-PLACE CONCRETE SPECIFICATION SECTION 2.6
 -AIR ENTRAINMENT SHALL CONFORM WITH MCDONALDS CAST-IN-PLACE CONCRETE SPECIFICATIONS SECTIONS 2.6-A & 2.13-A
 -WATER CONTENT RATIO SHALL CONFORM TO MCDONALDS CAST-IN-PLACE CONCRETE SPECIFICATIONS SECTION 2.13-A
 -FOUNDATION CONCRETE TO BE TESTED PER MCDONALDS CAST-IN-PLACE CONCRETE SPECIFICATIONS SECTION 3.14
 -PROVIDE A MINIMUM 3" OF CONCRETE COVER OVER ALL EMBEDDED STEEL.
 -REINFORCEMENT PLACEMENT SHALL CONFORM TO MCDONALDS CAST-IN-PLACE CONCRETE SPECIFICATIONS SECTIONS 3.2 & 3.5. PERFORMED BY GENERAL CONTRACTOR.
 -ANCHOR BOLTS TO BE SET IN ACCORDANCE WITH AISC CODE OF STANDARD PRACTICE
 -DO NOT PLACE POLES ON CONCRETE UNTIL CONCRETE HAS CURED PER MCDONALDS CAST-IN-PLACE CONCRETE SPECIFICATION, SECTION 3.11-E.

STEEL:

- STEEL PIPE SECTION: ASTM A53 OR A252 TYPE E GRADE B (Fy = 35ksi)
 -HSS ROUND SECTION: ASTM A500 GRADE B (Fy = 42ksi)
 -HSS SQUARE/RECTANGULAR SECTIONS: ASTM A500 GRADE B (Fy = 46ksi)
 -CONNECTION BOLTS A325
 -STEEL ANGLES, CHANNELS, STRUCTURAL SHAPES AND PLATES: ASTM A36
 -REINFORCEMENT: GRADE 60 - BY GENERAL CONTRACTOR
 -NUTS: A563DH OR A194-2H
 -WASHERS: A36
 -USE HOT DIPPED GALVANIZED BOLTS AND FASTENERS
 -ANCHOR RODS, NUTS, AND WASHERS SHALL BE SHIPPED AS AN ASSEMBLY FROM THE SIGN/LIGHTING MANUFACTURER

STATE OF MISSOURI	ROBERT E. FARNWORTH	PROFESSIONAL ENGINEER	NO. 0083
DATE: 12-28-17	REVISION: 1	DATE: 12-28-17	REVISION: 1
DESCRIPTION: city comments	BY: jpb	DATE: 12-28-17	REVISION: 1
PREPARED BY: Farnsworth Group, Inc. MISSOURI STATE CERTIFICATE OF AUTHORITY #001321 20 ALLEN AVENUE, SUITE 200 ST. LOUIS, MISSOURI 63119 (314) 962-7900 / (314) 962-1283 fax www.fw.com			
© 2011 McDonald's USA, LLC McDonald's USA, LLC These drawings and specifications are the confidential and proprietary property of McDonald's USA, LLC and are not to be reproduced, copied, or used in any manner without the express written consent of McDonald's USA, LLC. Use of these drawings and specifications for use on a different site or at a later time, or for any other purpose, is strictly prohibited. The use of the services of properly licensed architects and engineers, and reproduction of the contract documents for reuse on another project is not authorized.			
TITLE: STANDARD SITE DETAILS	DATE: JAN 2013	REVIEWED BY: FPP	DATE ISSUED: JAN 2013
ORDER HERE CANOPY	DESCRIPTION:	SITE ADDRESS:	STANDARD SITE DETAILS
SHEET NO: SD7			