

COMMERCIAL

GENERAL NOTES

GN # 1 Driveway locations shall not interfere with the sidewalk handicap ramps, or curb inlet ramps
 GN # 2 Sidewalks, curb ramps, ramps and accessible parking spaces shall be constructed in accordance with the current approved "American with Disabilities Act Accessibility Guidelines" (ADAAG) along with the required grades, construction materials, specifications and signage. If any conflict occurs between the above information and the plans, the ADAAG guidelines shall take precedence and the contractor prior to any construction shall notify the Project Engineer.

GN # 3 Transected zones for curb ramps located in public right of way shall meet ADA requirements and shall be constructed using red pre cast truncated domes per pavement details.

GN # 4 Any proposed pavilions or playground areas will need a separate permit from the Building Division.

GN # 5 The Contractor is responsible to call Minot One Call and The City of O'Fallon for the location of utilities. Contact the City of O'Fallon (656) 379-3814 for the location of City maintained cable for street lights and traffic signals, all other utilities call Minot One Call 1-800-DIG-RITE. 1-800-344-7483

GN # 6 All proposed utilities and/or utility relocation shall be located underground.

GN # 7 All proposed fencing requires a separate permit through the Planning and Development Division.

GN # 8 All construction operations and work zone traffic control within the right of way will follow MoDOT or M.U.T.C.D. standards whichever is more stringent.

GN # 9 All free standing signs shall be minimum of ten (10) feet away from any right of way line and/or property line and a minimum of three (3) feet from the back of curbing or sidewalk. All signs shall abide by the regulations for visibility at corners, including corners from driveways and the street it intersects per Section 400.260 of the O'Fallon Zoning Code.

GN # 10 All subdivision identification or directional sign(s) must have the locations and sizes approved and permitted separately through the Planning and Development Division.

GN # 11 Materials such as trees, organic debris, rubble, foundations, and other deleterious material shall be removed from the site and disposed of in compliance with all applicable laws and regulations. If the material listed previously are round, a letter from a soil Engineer must clearly state, location, depth, etc. and be approved with the construction plans. Landfill tickets for such disposal shall be maintained on file by the developer. Banning on site shall be allowed only by permit from the local fire district. If a burn pit is proposed the location and mitigation shall be shown on the grading plan and documented by the soils engineer.

GN # 12 Twenty-four (24) hours prior to starting any of the work covered by the above plans and after approval thereof, the developer shall make arrangements with the Construction Inspection Office to provide for inspection of the work, sufficient in the opinion of the City Engineer, to assure compliance with the plans and specifications as approved.

GN # 13 The City Engineer or their duly authorized representative shall make all necessary inspection of City infrastructure, escrow items or infrastructure located on the approved plans.

Erosion Control Notes

EN # 1 The Permittee shall assume complete responsibility for controlling all siltation and erosion of the project area. The Permittee shall use whatever means necessary to control erosion and siltation including, but not limited to, staked straw bales and/or siltation fabric fences (possible methods of control are detailed in the plans). Control shall commence with the clearing operation and be maintained throughout the project until acceptance of the work by City of O'Fallon and as needed by MoDOT. The Permittee's responsibilities include all design and implementation required to prevent erosion and the depositing of silt. The City of O'Fallon and as required by MoDOT may at their option direct the Permittee in his methods as deemed fit to protect property and improvements. Any depositing of silt or mud on new or existing pavement shall be removed immediately. Any depositing of silt or mud in new or existing storm sewers and/or vaults shall be removed after each rain and affected areas cleaned to the satisfaction of the City of O'Fallon and as required by MoDOT.

EN # 2 All erosion control systems are to be inspected and corrected weekly, especially within 48 hours of any rain storm resulting in one-half inch of rain or more. Any silt or debris leaving the site and affecting public right of way or storm water drainage facilities shall be cleaned up within 24 hours after the end of the storm.

EN # 3 Erosion control devices (site fence, sediment basin, etc.) shall be in accordance with St. Charles County Soil and Water Conservation Districts Erosion and Sediment Control guidelines.

EN # 4 This development is required to provide long term post construction BMP's such as, low impact design, source control and treatment controls that protects water quality and controls run off to maximum extent practical in compliance with Phase II illicit Storm Water Discharge Guidelines. (Ord. 5082, section 405.0245)

EN # 5 Graded areas shall be sealed and mulched (seeded) within 14 days of stopping land disturbance activities. Unless it can be shown to the City Engineer that weather conditions are not favorable, vegetative growth is to be established within 6 weeks of stopping grading work on the project. The vegetative growth established shall be sufficient to prevent erosion and the standard shall be as required by EPA and DNR. 70% coverage per square foot. Ord. 5242, Section 405.070

Grading Notes

GRN # 1 Developer must supply City construction inspectors with soil reports prior to and during site grading. The soil report will be required to contain the following information on soil test curves (Proctor report) for projects within the City:
 1. Maximum dry density
 2. Optimum moisture content
 3. Maximum and minimum allowable moisture content
 4. Curve must be plotted to show density from a minimum of 90% Compaction and above as determined by the "Modified ASHTO T-180 Compaction Test" (A.S.T.M.-D-1157) or from a minimum of 95% as determined by the "Standard Proctor Test ASHTO T-99, Method C" (A.S.T.M.-D-698). Proctor type must be designated on documents.
 5. Curve must have at least 3 density points with moisture content and sample locations listed on document
 6. Specific gravity
 7. Natural moisture content
 8. Liquid limit
 9. Plastic limit

Be advised that if this information is not provided to the City's Construction Inspector the City will not allow grading or construction activities to proceed on any project site.

GRN # 2 All fill placed in areas other than proposed storm sewers, sanitary sewers, proposed roads, and paved areas shall be compacted from the bottom of the fill up to 4" lifts and compacted to 90% maximum density as determined by Modified ASHTO T-180 compaction test or 95% of maximum density as determined by the Standard Proctor Test ASHTO T-99. Ensure the moisture content of the soil in fill areas corresponds to the compactive effort as defined by the Standard or Modified Proctor Test. Optimum moisture content shall be determined using the same test that was used for compaction. Soil compaction curves shall be submitted to the City of O'Fallon prior to the placement of fill.

GRN # 3 The surface of the fill shall be finished smooth. If the surface has been finished smooth for any reason, it shall be scarified before proceeding with the placement of succeeding lifts. Fill shall not be placed on frozen ground, nor shall filling operations continue when the temperature is such as to permit the layer under placement to freeze.

GRN # 4 All sediment and detention basins are to be constructed during the initial phase of the grading operation in accordance with the approved SWPPP.

GRN # 5 When grading operations are complete or suspended for more than 14 days, permanent grass must be established at sufficient density to provide erosion control on site. Between permanent grass seeding periods, temporary cover shall be provided according to St. Charles Soil and Water Conservation District - Model Sediment and Erosion Control Regulations. All finished grades (areas not to be disturbed by improvements) in excess of 20% slopes (5:1) shall be mulched and tacked at a rate of 100 pounds per 1000 square feet when needed.

GRN # 6 No slopes shall exceed 3 (horizontally 1 vertical) unless otherwise approved by the soils report and specifically located on the plans and approved by the City Engineer.

GRN # 7 All low places whether on site or off shall be graded to provide drainage with temporary ditches.

GRN # 8 All existing wells site shall be capped per DNR standards.

Grading Notes Continued

GRN # 10 All trench back fills under paved areas shall be granular back fill, and compacted mechanically. All other trench back fills may be earth material (free of large clods, or stones) and compacted using either mechanical or water jetting. Granular material and earth material associated with new construction outside of pavements may be jetted, taking care to avoid damage to newly laid sewers. The jetting shall be performed with a probe reuse on not greater than 7.5 foot centers with the jetting probe centered over and parallel with the direction of the pipe. Trench widths greater than 10 feet will require multiple probes every 7.5 foot centers.

a) Depth, Trench back fills less than 8 feet deep shall be probed to a depth extending half the depth of the trench back fill, but not less than 3 feet. Trench back fill greater than 8 feet in depth shall be probed to half the depth of the trench back fill but not greater than 8 feet.

b) Equipment, The jetting probe shall be a metal pipe with an interior diameter of 1.5 to 2 inches.

c) Method, Jetting shall be performed from the lowest surface topographic point and proceed toward the highest point, and from the bottom of the trench back fill toward the surface. The flooding of each jetting probe shall be spaced slowly allowing dewatering of the soil. Water is not allowed to flow away from the trench without first saturating the results.

d) Surface Bridging, The contractor shall identify the locations of the surface bridging (the tendency for the upper surface to crust and arch over the trench rather than collapse and consolidate during the jetting process). The contractor shall break down the bridged areas using an appropriate method such as wheel or beater or a backhoe. When surface crust is collapsed, the void shall be back filled with the same material used as trench back fill and recompacted. Compaction of the materials within the backfilled/poured area shall be compacted such that no further surface subsidence occurs.

GRN # 11 Site grading.

a. Within City right-of-way. Material is to be placed in eight (8) inch to twelve (12) inch loose lifts and compacted per the approved compaction requirements. One (1) compaction test will be performed every two hundred fifty (250) feet along the centerline for each lift.

b. Outside of City right-of-way. Material is to be placed in eight (8) inch to twelve (12) inch loose lifts and compacted per the approved compaction requirements. One (1) compaction test will be performed at two (2) foot vertical intervals and approximately every one thousand (1,000) cubic yards.

Sanitary Sewer Notes

SAN # 1 All sanitary sewer installations is to be in accordance with M.S.D. 2009 standards and specifications except as modified by the City of O'Fallon Ordinances.

SAN # 2 Brick shall not be used in the construction of sanitary sewer structures. Pre cast concrete structures are to be used unless otherwise approved by the City of O'Fallon.

SAN # 3 Connections at all sanitary structures are to be made with A-Lock joint or equal

SAN # 4 All sanitary lateral shall be a minimum of 4" residential, 6" commercial diameter pipe.

SAN # 5 All sanitary main shall be a minimum of 8" diameter pipe.

SAN # 6 All sanitary sewer line with a slope greater than 20% will require concrete cradle or concrete collar. Sanitary line with a slope greater than 50% will require a special approved design as shown on detail sheet.

SAN # 7 All manholes built within 100' from pool must have lock type watertight manhole covers.

SAN # 8 All sanitary sewer mains must have a minimum of 4" cover.

SAN # 9 When sanitary mains cross over storm the sanitary main must be buried iron pipe for 10ft on each side of the crossing.

SAN # 10 Encase with concrete both sanitary and storm sewer at crossing when storm sewer is within 18 inches above sanitary sewer. Add concrete cradle to only RCP storm sewer and encase HOPE storm sewer when it is more than 18 inches above sanitary line. Show on profile sheet.

SAN # 11 The sanitary sewer should be diagonal through the side yards to minimize any additional utility easements required.

SAN # 12 All sanitary pipes shall be wastewater in accordance to Missouri DNR specifications 10CSR-8.120 (7)(E).

SAN # 13 All sanitary sewer pipe shall be SDR35 or equal.

SAN # 14 All sanitary manholes and pipes will be tested to the following specifications. ASTM C1244, Standard testing method for Concrete Sewer Manhole by Negative Air Pressure (Vacuum). Laser revision ASTM F1417, Standard testing method for Installation Acceptance of Plastic Gravity Sewer Lines Using Low Pressure Air, Laser revision.

SAN # 15 Add 1" minus rock back fill to all sanitary sewer and all other utilities that lie within the 1:1 shear plane of the road.

Storm Sewer Notes

STM # 1 All Storm Sewer installation is to be in accordance with M.S.D. 2009 standards and specifications except as modified by the City of O'Fallon ordinances.

STM # 2 Brick shall not be used in the construction of storm sewer structures. Pre cast concrete structures are to be used unless otherwise approved by the City of O'Fallon.

STM # 3 A 5/8" drain shall be installed horizontally in the center of the opening(s) in all curb inlets and area inlets.

STM # 4 HDPE pipe is to be N=12WT or equal and to meet ASTM F1417 water tight field test.

STM # 5 Encase with concrete both sanitary and storm sewer at crossing when storm sewer is within 18 inches above sanitary sewer. Add concrete cradle to only RCP storm sewer and encase HOPE storm sewer when it is more than 18 inches above sanitary line. Show on profile sheet.

STM # 6 The storm sewer should run diagonally through the side yards to minimize any additional utility easements required.

STM # 7 All concrete pipes will be installed with O-ring rubber type gaskets.

STM # 8 Connection at all storm structures are to be made with A-lock joint or equal.

STM # 9 For concrete inlets covers are not to be used.

STM # 10 The valve in the detection shaft shall have a minimum 1% longitudinal slope and be lined with a permanent erosion control blanket that will allow infiltration of storm water.

STM # 11 All storm sewer shall be reinforced concrete pipe or H.D.P.E. pipe. All structures and flared sections must be concrete. Manufacturing specifications must be followed and details provided for the installation of H.D.P.E. pipe. H.D.P.E. pipe will not be allowed for detention basin outlets, final pipe run to detention basins, creek discharge or other approved means.

STM # 12 The discharge point of all flared end sections shall be protected by rip rap or other approved means.

STM # 13 Rip rap at flared end sections will be evaluated in the field by the Engineers, Contractor, and City Inspectors after installation for effectiveness and field modified, if necessary to reduce erosion on and off site.

STM # 14 Add 1" minus rock back fill to all storm sewer that lie within the 1:1 shear plane of the road.

Water Notes

WN # 1 Fire hydrants shall be a minimum of 60' apart. Local fire district approval is required.

WN # 2 Coordinate with the water company on the location of water meters.

WN # 3 All water main must have a minimum of 4" of cover. (City water main)

WN # 4 Provide valves to isolate the system.

WN # 5 All water mains shall class 200 SDR 21 or equal with locator/tracer wires.

WN # 6 DISINFECTION:

Disinfecting shall be accomplished by placing sufficient hypo chlorine granule (HTH) in each section of pipe to achieve a chlorine residual in the pipeline, upon initial filling, of 50 mg/l (PPM). HT, tablets will not be allowed. Following completion of the pipeline, it shall be slowly filled with water and a sample will be taken immediately and the chlorine residual must be 50 mg/l or greater. The solution shall be allowed to stand for 24 hours and a sample shall then be taken. The chlorine residual after 24 hours shall be 30 mg/l or greater. If the piping shows insufficient chlorine residuals in either test, the piping shall be re-chlorinated by the injection of hypo chlorine solution until satisfactory results are achieved. All disinfecting shall be done by the contractor. Only the testing to determine the chlorine residual will be done by the City.

WN # 7 PRESSURE TESTING:

Immediately following disinfection, the piping shall be pumped to a pressure (at the lowest point in the project) of 150 psi or higher where the working pressure is higher than 150 psi as determined by the City. In such cases, the pressure shall be as specified by the City and two pressure tests shall be conducted. The first test shall be with the fire hydrant auxiliary valve open and set to 150 PSI. The second test shall be with the fire hydrant auxiliary valve closed and to the higher pressure as directed by the City. All pumping equipment and pressure gauges shall be provided by the contractor. After achieving the set pressure, the piping shall be left closed for a period of two (2) hours. At the end of this time the pressure drop shall not exceed 2 psi. In addition, if the pressure appears, in judgment of the City's representative, to be continuing to drop, the contractor shall be continued for another two (2) hours and if any further drops occur, the contractor shall be considered a failure. If the pressure test fails, the contractor will be required to find and correct the source of the leakage. If this requires draining of the pipeline, when the leakage is corrected, the pipeline must be re-disinfected and the pressure tested again until satisfactory results are achieved. Any MDNR required dechlorination will be performed by the contractor.

WN # 8 All tops for valves, meters, and manholes are to be constructed to within 1 inch (0.08") of finish grade. Grading around structure tops on slopes need to be accounted for.

Water Notes

WN # 10 BACTERIOLOGICAL TESTING:

After satisfactory disinfection and pressure testing, a sample shall be taken by the contractor in the presence of a City representative and submitted to a laboratory approved by the Missouri Department of Natural Resources and the City for bacteriological analysis. After 24 hours, a second sample shall be taken in a like manner and submitted for analysis. The two samples taken on consecutive days, a minimum of 24 hours apart, must be found to be "safe" by the testing laboratory, and copies of the test results must be supplied to the City. If the samples are not found to be "safe" further flushing and/or disinfection as directed by the City shall be conducted by the contractor until "safe" samples on two consecutive test days are achieved. Following successful bacteriological testing and a determination by the City that the samples are "safe", the mains may be placed into service.

Roadway Notes

RN # 1 All paving (public and private) to be in accordance with 2006 St. Charles County Standards and Specifications except as modified by the City of O'Fallon ordinances.

RN # 2 If the intersecting road does not have a curb, then the curb on the new entrance shall begin 10' from the edge of the existing road.

RN # 3 Provide 6" of concrete over 4" of MoDot type 1 or type 5 aggregate rock or asphalt equivalent for minor residential areas per City Code 405.370.

RN # 4 Multi-use trail (when required) Shall have a minimum of 3" Type "C" Asphalt over 4" aggregate base per City requirements.

RN # 5 Type C (BP-1) Compaction requirements shall be 98% minimum density according to St. Charles Co. Standard Specifications.

RN # 6 Provide pavement melting at any point where the multi-use trail crosses existing or proposed pavement.

RN # 7 All street sub-grade or cut or fill will need to conform to the City of O'Fallon Compaction requirements.

RN # 8 All paving sub-grade or cut or fill will require a thickness of 10" to 12" of concrete.

RN # 9 Material Testing And Frequency. Materials for construction shall be tested and inspected per the appropriate ASTM code or at the City Engineer's discretion. The developer's engineer shall perform the following quality control procedures:

1. Concrete.

a. Cylinders/compressive strength. One (1) set of four (4) cylinders within the first fifty (50) cubic yards and one (1) set per one hundred (100) cubic yards thereafter. One (1) cylinder must be tested at seven (7) days, one (1) at fourteen (14) days and two (2) at twenty-eight (28) days. If the first (1x) cylinder does not meet specifications at twenty-eight (28) days, then the second (2nd) cylinder must be held and tested at day fifty-six (56).

b. Permeability. First (1x) truck batch each day and two (2) thereafter until a consistency is encountered. Once a consistency is encountered, then tests will be performed in conjunction with the concrete cylinders.

c. Slump. First (1x) truck batch each day and two (2) thereafter until a consistency is encountered. Once a consistency is encountered, then tests will be performed in conjunction with the concrete cylinders.

d. Shrinkage. If concrete is