

ACREAGE:
ON-SITE 6.17 ac
OFF-SITE 4.66 ac
TOTAL 10.83 ac

RUNOFF:
2yr storm 10.83 ac x 1.61 = 17.44 cfs
15yr storm 10.83 ac x 2.64 = 28.33 cfs
25yr storm 10.83 ac x 3.26 = 34.98 cfs
100yr storm 10.83 ac x 4.17 = 44.74 cfs

ATTENUATION:
2yr storm 6.17 ac x (1.61 - 1.15) = 2.84 cfs
10.83 ac x (1.61 - 1.15) = 4.98 cfs

15yr storm 6.17 ac x (2.64 - 1.87) = 4.75 cfs
10.83 ac x (2.64 - 1.87) = 8.34 cfs

25yr storm 6.17 ac x (3.26 - 2.31) = 5.86 cfs (required)
10.83 ac x (3.26 - 2.31) = 10.29 cfs

100yr storm 6.17 ac x (4.17 - 2.95) = 7.53 cfs
10.83 ac x (4.17 - 2.95) = 13.21 cfs

AVONDALE HEIGHTS - PLAT FIVE
DETENTION ANALYSIS
BASIN B
2 YEAR STORM

INITIAL CONDITIONS: Elevation = 495.00 ft, Outflow = 0.00 cfs, Storage = 0 cu-ft. GIVEN POND DATA table with columns: ELEVATION (FT), OUTFLOW (CFS), STORAGE (CU-FT). INTERMEDIATE ROUTING COMPUTATIONS table with columns: 25% (CFS), 25% + 0 (CFS).

AVONDALE HEIGHTS - PLAT FIVE
DETENTION ANALYSIS
BASIN B
15 YEAR STORM

INITIAL CONDITIONS: Elevation = 495.00 ft, Outflow = 0.00 cfs, Storage = 0 cu-ft. GIVEN POND DATA table with columns: ELEVATION (FT), OUTFLOW (CFS), STORAGE (CU-FT). INTERMEDIATE ROUTING COMPUTATIONS table with columns: 25% (CFS), 25% + 0 (CFS).

AVONDALE HEIGHTS - PLAT FIVE
DETENTION ANALYSIS
BASIN B
25 YEAR STORM

INITIAL CONDITIONS: Elevation = 495.00 ft, Outflow = 0.00 cfs, Storage = 0 cu-ft. GIVEN POND DATA table with columns: ELEVATION (FT), OUTFLOW (CFS), STORAGE (CU-FT). INTERMEDIATE ROUTING COMPUTATIONS table with columns: 25% (CFS), 25% + 0 (CFS).

AVONDALE HEIGHTS - PLAT FIVE
DETENTION ANALYSIS
BASIN B
100 YEAR STORM

INITIAL CONDITIONS: Elevation = 495.00 ft, Outflow = 0.00 cfs, Storage = 0 cu-ft. GIVEN POND DATA table with columns: ELEVATION (FT), OUTFLOW (CFS), STORAGE (CU-FT). INTERMEDIATE ROUTING COMPUTATIONS table with columns: 25% (CFS), 25% + 0 (CFS).

AVONDALE HEIGHTS - PLAT FIVE
DETENTION ANALYSIS
BASIN B
Planimeter scale: 1 inch = 1 ft.

Table with columns: Elevation (ft), Planimeter (sq. in.), Area (sq. ft), Altitude (ft), Volume (cu-ft), Volume Sum (cu-ft).

Incremental volume computed by the Conic Method for Reservoir Volumes.

COMPOSITE OUTFLOW SUMMARY table with columns: Elevation (ft), Q (cfs), Contributing Structures.

ROUTING COMPUTATIONS table with columns: TIME (min), INFLOW (cfs), 11+12 (cfs), 25% - 0 (cfs), 25% + 0 (cfs), OUTFLOW (cfs), ELEVATION (ft).

SYSTEM CONNECTIVITY table with columns: Structure No., Q Table, Q Table.

DRIFICE - Based on Area and Datum Elevation. Table with columns: Elevation (ft), Drifice coeff., Invert elev. (ft), Datum elev. (ft), Drifice area (sq. ft).

Summary of Peak Outflow and Peak Elevation. Summary of Approximate Peak Storage.

DRIFICE - Based on Area and Datum Elevation. Table with columns: Elevation (ft), Drifice coeff., Invert elev. (ft), Datum elev. (ft), Drifice area (sq. ft).

Summary of Peak Outflow and Peak Elevation. Summary of Approximate Peak Storage.

ROUTING COMPUTATIONS table with columns: TIME (min), INFLOW (cfs), 11+12 (cfs), 25% - 0 (cfs), 25% + 0 (cfs), OUTFLOW (cfs), ELEVATION (ft).

Summary of Peak Outflow and Peak Elevation. Summary of Approximate Peak Storage.

DRIFICE - Based on Area and Datum Elevation. Table with columns: Elevation (ft), Drifice coeff., Invert elev. (ft), Datum elev. (ft), Drifice area (sq. ft).

Summary of Peak Outflow and Peak Elevation. Summary of Approximate Peak Storage.

ROUTING COMPUTATIONS table with columns: TIME (min), INFLOW (cfs), 11+12 (cfs), 25% - 0 (cfs), 25% + 0 (cfs), OUTFLOW (cfs), ELEVATION (ft).

Summary of Peak Outflow and Peak Elevation. Summary of Approximate Peak Storage.

DRIFICE - Based on Area and Datum Elevation. Table with columns: Elevation (ft), Drifice coeff., Invert elev. (ft), Datum elev. (ft), Drifice area (sq. ft).

Summary of Peak Outflow and Peak Elevation. Summary of Approximate Peak Storage.

ROUTING COMPUTATIONS table with columns: TIME (min), INFLOW (cfs), 11+12 (cfs), 25% - 0 (cfs), 25% + 0 (cfs), OUTFLOW (cfs), ELEVATION (ft).

Summary of Peak Outflow and Peak Elevation. Summary of Approximate Peak Storage.

DRIFICE - Based on Area and Datum Elevation. Table with columns: Elevation (ft), Drifice coeff., Invert elev. (ft), Datum elev. (ft), Drifice area (sq. ft).

Summary of Peak Outflow and Peak Elevation. Summary of Approximate Peak Storage.

ROUTING COMPUTATIONS table with columns: TIME (min), INFLOW (cfs), 11+12 (cfs), 25% - 0 (cfs), 25% + 0 (cfs), OUTFLOW (cfs), ELEVATION (ft).

Summary of Peak Outflow and Peak Elevation. Summary of Approximate Peak Storage.

DRIFICE - Based on Area and Datum Elevation. Table with columns: Elevation (ft), Drifice coeff., Invert elev. (ft), Datum elev. (ft), Drifice area (sq. ft).

Summary of Peak Outflow and Peak Elevation. Summary of Approximate Peak Storage.

ROUTING COMPUTATIONS table with columns: TIME (min), INFLOW (cfs), 11+12 (cfs), 25% - 0 (cfs), 25% + 0 (cfs), OUTFLOW (cfs), ELEVATION (ft).

Summary of Peak Outflow and Peak Elevation. Summary of Approximate Peak Storage.

DRIFICE - Based on Area and Datum Elevation. Table with columns: Elevation (ft), Drifice coeff., Invert elev. (ft), Datum elev. (ft), Drifice area (sq. ft).

Summary of Peak Outflow and Peak Elevation. Summary of Approximate Peak Storage.

BLOCK CHECK: H = [44.74 / (11.67)]^2/3 = 1.18 ft. FREEBOARD = 502 - (499.25 + 1.18) = 1.57 ft.