

SECOND FLOOR FIRE PROTECTION - SOUTH WING

## KEYED NOTES

- 1 POINT OF CONNECTION FOR FEED MAIN TO EAST LOBBY SPRINKLERS.
- 2 PROVIDE TWO (2) HEADS IN STORAGE ROOM AND TWO (2) HEADS FOR FIRST FLOOR AREA BENEATH STORAGE ROOM.

## GENERAL NOTES:

- PROVIDE A WET PIPE AUTOMATIC SPRINKLER SYSTEM INSTALLED IN COMPLIANCE WITH THE LATEST APPLICABLE EDITION OF NFPA 13.
- FINAL SPRINKLER HEAD SELECTION AND LOCATION IS THE RESPONSIBILITY OF THE SPRINKLER CONTRACTOR AND SHALL BE IN ACCORDANCE WITH NFAP 13 AND THE MANUFACTURERS LISTING.
- COORDINATE FINAL LOCATION OF SPRINKLER HEADS WITH LIGHTS, DIFFUSERS, GRILLE, ETC.

Date SEPT. 4, 1997 Designed

CONSTRUCTION ISSUE

DECEMBER 5, 1997

CHANGE ORDER NO. 1 JANUARY 27, 1998

CONSTRUCTION

**DOCUMENTS**