

## KEYED NOTES (THIS SHEET ONLY)

- 1 HOLD HEAT PUMP AS HIGH AS POSSIBLE (TYP.). SEE SECTION THRU CORRIDOR.
- 2 HOLD FRESH AIR DUCT AS HIGH AS POSSIBLE. SEE SECTION THRU CORRIDOR.
- 3 DUCTWORK ABOVE CEILING (TYP.).
- 4 14x12 RETURN AIR OPENING IN PARTITION ABOVE CEILING.
- (5) RETURN AIR SOUND TRAP ABOVE CEILING (TYP.).
- 6 THIS AREA IS USED AS A RETURN AIR PLENUM. SEAL AIR TIGHT ALL AROUND.
- SUPPLY AND RETURN DUCT TO HP-2-8. SEE SHEET H-9 FOR CONTINUATION.
- 8 THERMA-FUSER. SEE AIR DEVICE SCHEDULE.
- 9 8" DUCT TO THIRD FLOOR. SEE THIRD FLOOR PLAN.
- (10) 2"# CONDENSATE DRAIN SHALL BE TERMINATED TO MOP SINK IN JANITORS CLOSET.
- (11) 3"Ø CWS AND CWR PIPING IN NEAREST WALL.



CONSTRUCTION ISSUE DECEMBER 5, 1997

CONSTRUCTION Drawing No. DOCUMENTS