



MAINTAINED FOOTCANDLE VALUES AT GRADE,
USING A .72 MAINTENANCE FACTOR.

NOTE: ALL 20' POLES TO BE MOUNTED ON CONCRETE PEDESTALS
2' ABOVE GRADE FOR A TOTAL MOUNTING HEIGHT OF 22'.

THIS IS NOT AN LSI RECOMMENDED LIGHT LAYOUT.
LSI IS NOT RESPONSIBLE FOR SAFETY AND
SECURITY RISKS DUE TO INADEQUATE LIGHT LEVELS.

Statistical Area Summary					
Label	Avg	Max	Min	Avg/Min	Max/Min
INSIDE CURB	4.34	13.7	0.5	8.68	27.40

Luminaire Schedule							
Symbol	Qty	Label	Arrangement	Lumens	LLF	Description	Total Watts
➔	9	B	SINGLE	32000	0.720	CTM-FT-400-MH-F-MT-BRZ-HSS / 4SQBD-S11G-20-S-BRZ-4BC	458

Conditions
architect must
conditions.
Site data
may vary due to
conditions.

Rev.	Date	By
3	11-15-04	BDB
2	10/19/04	LLS
1	10/12/04	LLS

Revisions

LSI INDUSTRIES™
WWW.LSI-INDUSTRIES.COM • P.O. BOX 4000 • CHICAGO, ILL. 60640
 (815) 750-0800 • FAX (815) 750-0805

LIGHTING PROPOSAL FOR
 DEL TACO
 D'FALLON, MD

SCALE: 1"=20'
 DATE: 10/7/04
 BY: LLS SHEET 1 OF 1