

Note: Temporary silt control device shall be inserted into end of permanent storm sewer pipe and used as overflow structure until such time as the grading and construction has been completed. Once vegetation has established and before site is occupied, the detention basin shall be mucked of all silt, sodded, and permanent overflow structure constructed.


TEMPORARY SILTATION CONTROL DEVICE

Note: Temporary silt control device shall be inserted into end of permanent storm sewer pipe and used as overflow structure until such time as the grading and construction has been completed. Once vegetation has established and before site is occupied, the detention basin shall be mucked of all silt, sodded, and permanent overflow structure constructed.

LEGEND  
 UFL = UPSTREAM FLOW LINE  
 DFL = DOWNSTREAM FLOW LINE

TEMPORARY SILTATION CONTROL DEVICE

NOTE: ALL STORM SEWERS TO BE PRIVATE  
 SCALE: 1" = 40' HORIZ.  
 1" = 5' VERT.



REVISIONS

**STORM SEWERS PROFILES  
 DELMAR GARDENS**

Delmar H and Twin Chimney Boulevard  
 07/10/10, Missouri 63166

Prepared for:  
**DELMAR GARDENS ENTERPRISES, INC.**  
 101 South Hanley Road  
 St. Louis, Missouri 63105  
 (314) 862-0045

Designed: SLH  
 Drawn: MRW  
 Checked: MCH  
 Date: 05/21/02  
 Project Number: 00228.1  
 Sheet Number: C-11 of 16

the clayton engineering company, inc.  
 ENGINEERS + SURVEYORS + PLANNERS  
 11900 WESTLINE INDUSTRIAL DRIVE  
 ST. LOUIS, MISSOURI 63146  
 (314) 692-8688 FAX: (314) 692-8688  
 clayton-engineering.com