



A CURB AND GUTTER SYSTEM MUST BE INSTALLED BEHIND THE WALL TO INTERCEPT ALL RUNOFF AND DIRECT IT TO THE STORM SYSTEM.

NOTE: A CURB AND GUTTER SYSTEM MUST BE INSTALLED BEHIND THE WALL TO INTERCEPT ALL RUNOFF AND DIRECT IT TO THE STORM SYSTEM.

STRUCTURAL DESIGN HEREIN REPRESENTS A FINISHED STRUCTURE. THE GENERAL CONTRACTOR/OWNER SHALL PROVIDE ALL INTERIM BRACING, SHORING, INTERIM DRAINAGE PROVISIONS, DRAINAGE DIVERSION AND EROSION PROTECTION REQUIRED UNTIL FINAL CAPPING, PAVING, CURBING AND COMPLETION OF FINAL STORM DRAIN SYSTEM IS COMPLETE.

1 PLAN VIEW OF WALLS 1, 2 & 3
PI SCALE: 1"=20'-0"

THIS WALL PLAN IS INTENDED FOR GENERAL LOCATION PURPOSES ONLY. REFER TO PROJECT SITE PLANS FOR SPECIFIC DIMENSIONS.

THESE PLANS ARE FOR THE EXCLUSIVE USE OF ROSCH CONSTRUCTION. USE OF THESE PLANS BY ANY OTHER ENTITY TO CONSTRUCT THE SUBJECT STRUCTURES WILL RENDER THE ENGINEERING SEAL SHOWN NULL AND VOID.

REV	DATE	DESCRIPTION
3	7-13-23	DESIGN REVISION - SUBMITTAL COMS
2	6-28-23	NO CHANGES THIS SHEET
1	5-9-23	DESIGN REVISION - RCO 2

ROSCH ENGINEERING
 18390 WINGS CORPORATE DRIVE
 CHESTERFIELD, MO 63005
 PHONE: 636-519-7770
 FAX: 636-532-7773

DOLLAR GENERAL
 O'FALLON, MO
 RETAINING WALL
 PLANS

DESIGNED:	BCS
DRAWN:	JTM
DESIGN ENGINEER:	ECS
REVIEWED:	BCS
DATE:	3-27-23
JOB NO.:	22-1048
SHEET:	PI

