- 1. Underground utilities have been plotted from available information and therefore their locations shall be considered approximate only. The verification of the location of all underground utilities, either shown or not shown on these plans, shall be the responsibility of the contractor, and shall be located prior to any grading and/or construction of improvements.
- 2. Erosion control shall not be limited to what is shown on the plans. The contractor shall take whatever means necessary to prevent siltation from entering adjacent roadways, properties, and ditches. Such control might include channeling runoff into sediment basins, channeling runoff into areas where an extra row of strow bales are used. A silt fence might be considered, if necessary.
- 3. No area shall be cleared without permission of the developer.
- 4. Owner/Developer assumes full responsibility as to the performance of the grading operation and assurance that all properties and County and State roads will be
- 5. Soil preparation and re-vegetation shall be performed occording to Appendix A of the Model Sediment and Erosian Control Regulations for Urban Development.
- 5. Where natural vegetation is removed during grading, vegetation shall be re-established in such a density as to prevent erosion. Permanent type grasses shall be established as soon as possible or during the next seeding period after grading has been completed. Refer to Appendix A of St. Charles Soil and Water Conservation District - Model Sediment and Erosion Control Regulations.
- 7. Site preparation includes the clearance of all stumps, trees, bushes, shrubs, and weeds, the grubbing and removal of roots and other surface obstructions from the site; and the demolition and removal of any man-made structures. The unsultable material shall be properly disposed of off-site. Topsoll and grass in the fill areas shall be thoroughly disced prior to the placement of any fill. The Soils Engineer shall approve the discing operation.
- 8. Compaction equipment shall consist of tamping rollers, pneumatic-tired rollers, vibratory rollers or high speed impact type drum rollers acceptable to the Solle Engineer. The rollers shall be designed so as to avoid the creation of a layered fill without proper blending of successive fill layers.
- 9. The Soils Engineer shall observe and test the placement of the fill to verify that specifications are met. A series of fill density tests will be determined an each lift of fill. Interim reports showing fill quality will be made to the Owner at regular intervals. Developer must supply City Construction inspectors with soils report prior to or during site soil testing.
- 10. The Solis Engineer shall notify the Contractor of rejections of a lift of fill or portion thereof. The Contractor shall rework the rejected portion of fill and obtain notification from the Solis Engineer of its acceptance prior to the placement of
- 11. All Areas to receive fill shall be scarified to a depth of not less than 6 inches and then compacted to at least 85 percent of the maximum density as determined by the Modified AASHTO T-1800 Compaction Test (ASTM-D1557). Natural slopes steeper than 1 vertical to 5 horizontal to receive fill shall have horizontal benches cut into the slopes before the placement of any fill. The width and height to be determined by the Solis Engineer. The fill shall be loosely placed in horizontal layers not exceeding 8 inches in thickness and compacted in accordance with the specifications given below. The Soils Engineer shall be responsible for determining the acceptability of soils placed. Any unacceptable soils placed shall be removed at the Contractor's expense.
- 12. The sequence of operation in the fill greas will be; fill, compact, verify acceptable soil density, and repetition of the sequence. The acceptable moisture contents during the filling operation are those at which satisfactory dry densities can be obtained. The acceptable moisture contents during the filling operation in the remaining areas are from 2% to 8% above the optimum maisture content.
- 13. The surface of the fill shall be finished so that it will not impound water. If at the end of a days work it would appear that there may be rain prior to the next working day, the surface shall be finished smooth. If the surface has been finished smooth for any reason, it shall be scarified before proceeding with the placement of succeeding lifts. Fill shall not be placed on frozen ground, nor shall filling operations continue when the temperature is such as to permit the layer under placement to
- 14. All cut and fill slopes should be a maximum of 33% slope (3:1) after grading.
- 15. All fill including filled places under proposed storm and sanitary sewer lines and paved areas including trench backfills within and off the road right-of-way shall be compacted to 90% of maximum density as determined by the "Modified AASHTO T-180 Compaction Test (ASTM D1557)". All tests shall be verified by a Soils Engineer concurrent with grading and backfilling operations. The compacted fill shall be free of rutting and shall be non-yielding and non-pumping during proof rolling and
- 16. Fill placed within proposed street R.O.W. shall be compacted to 90% M.O.D. Proctor and be 2% below to 6% above optimum moisture content.
- 17. Soft soil in the bottom and banks of any existing or former pand site should be removed, spread out and permitted to dry sufficiently to be used as fill. None of this material should be placed in proposed right-of-way locations or on storm sewer
- 18. Temporary siltation control measures (structural) shall be maintained until vegetative cover is established at a sufficient density to provide erasion control on the
- 19. If strow bales or silt fences are destroyed by heavy rains, vandalism, etc., they are to be replaced immediately by contractor.
- 20. When grading operations are completed or suspended for more than thirty (30) days, permanent grass must be established at sufficient density to provide erosion control on the site. Between permanent gross seeding periods, temporary cover shall tie provided according to the Designated Official's recommendation. Refer to Appendix A of St. Charles Soil and Water Conservation District - Model Sediment and Erosian Control Regulations. All finished grades (areas not to be disturbed by improvement) in excess of 20% slopes (5:1) shall be mulched and tacked at the rate of 1 pounds per 1000 square feet when seeded.
- 21. All existing trash and debris on-site must be removed and disposed of off-site.
- 22. Debris and foundation material from any existing on-site building or structure which is scheduled to be razed for this development must be disposed of off-site.
- 23. The total yardage of this project is based on a 15% ± shrinkage factor.
- 24. The shrinkage factor is subject to change, due to sail conditions (types and maisture content), weather conditions, and the percentage of compaction actually achieved at the time of the year grading is performed. As a result, adjustments in final grade may be required. If adjustments need to be made, the contractor shall contact St. Charles Engineering and Surveying prior to completion of the grading.
- 25. Earth quantities were obtained from aerial grid mapping with contours at two foat intervals, with a tolerance of plus or minus one foot or one-half (2) contour intervals.
- 26. The vertical grading tolerance shall be plus or minus 0.2 feet for all rough
- 27. The Contractor shall prevent all storm/surface water, mud or construction debris from entering the existing sonitory sewer system.
- 29. The most stringent of the above requirements shall apply.
- 29. Water for wash-off pod will be brought onto site by truck until such time that water can be provided through existing water lines.
- 30. Coordination between the on-site grading of this project with any grading being done on the O'Fallan Road Improvement Project is required.
- 31. Each fire hydrant shall be provided with a control valve in the hydrant connection such that the hydrant can be removed from service without shutting off water supply
- 32. Each fire hydrant shall have not less than two 2-1/2 inch outlets and one 4-1/2 inch outlet, a 5-1/4 inch valve, a 6 inch barrel and shall be of the breakaway design, frost free chain, left hand open design and have National Standard Threads.

- 33. Developer must supply City construction inspectors with solls reports prior to or during site soil testing.
- 34. Sidewalks, curb ramps, ramp and accessible parking spaces shall be constructed in accordance with the current approved "American with Disabilities Act Accessibility Guidelines" (ADAAG) along with required grades, construction materials, specifications and signage. If any conflict occurs between the above information and the plans, the ADAAG guidelines shall take precedence and the contractor prior to any construction shall notify the Project Engineer. (Ensure at least one 8' wide handicap access aisle is provided and curb ramps do not project into handicap access aisle.)
- 35. All sign and entrance manument locations and sizes must be approved separately through the Planning Division.
- 36. All proposed utilities shall be located underground.
- 37. 5/8" trash bar shall be included on all inlets.
- 38. Any part of the existing O'Fallon Rd Right of Way that is to be vocated and povement that is to be removed will be handled by St. Charles County. None of the vacated land is anticipated to be deeded to any of the Hidden Creek Lots or Common
- 39. According to Flood Insurance Rate Map (FIRM) Panel Number 29183C435 E Dated August 2, 1996 the Northern Portion of this Plat is in the FEMA Regulated Floodplain and FloodWay.
- 40. St. Charles County Highway Department shall be notified 24 hours prior to the start of construction. Contact Vance Cribble, Chief Inspector, at 636-949-7305.
- 41. A Special Use Permit shall be obtained from St. Charles County Highway Department before any work is preformed within O'Fallon Rd right of way. Contact Donna C. Ray, Highway Project Engineer, at 636-949-7305.
- 42. Rip rap shown on at flared ends will be evaluated in the field after installation for effectiveness and field modified if necessary to reduce erosion of the existing and new

DUCKETT CREEK SANITARY DISTRICT CONSTRUCTION NOTES


- 1. Underground utilities have been plotted from available information and therefore location shall be considered approximate only. The verification of the location of all underground utilities, either shown or not shown on these plans, shall be the responsibility of the contractor and shall be located prior to any gradion or construction of improvements.
- 2. Gas, water, and other underground utilities shall not conflict with the depth or horizontal location of existing or proposed sonitary and storm sewers, including house laterals.
- 3. All existing site improvements disturbed, domaged or destroyed shall be repaired or replaced to closely match pre-construction conditions.
- 4. All fill including places under proposed storm and sanitary sewer lines and paved areas including trench backfills within and off the road right-of-way shall be configacted to 90 percent of maximum density as determined by the "Modified AASHTO T-180 Compaction Test (ASTM D1557)". All tests shall be verified by a Soils Engineer concurrent with grading and backfilling operations. The compacted fill shall be free of rutting and shall be non-yielding and non-pumping during proofrolling and
- 5. The contractor shall prevent all storm, surface water, mud and construction debris form entering the existing sanitary sewer system.
- 6. All sanitary sewer flowlines and tops built without elevations furnished by
- the engineer will be the responsibility of the sewer contractor. 7. Easements shall be provided for all sanitary sewers, storm sewers and all
- 8. All construction and materials shall conform to the current construction
- standards of the Duckett Creek Sanitary District. 9. The Duckett Creek Sanitary District shall be notified at least 48 hours prior to construction for coordination of inspection.
- 10. All sonitory sewer building connections shall be designed so that the minimum vertical distance from the low point of the pasement to the flowline of a sanitary sewer at the corresponding building connection shall not be less than the diameter of the pipe plus the vertical distance of 2-
- 11. All sanitary sewer manholes shall be waterproofed on the exterior in accordance with Missouri Dept. of Natural Resources Specification 10 CSR-8.120(7)(E).
- 12. All PVC sanitary sewer pipe shall conform to the requirements of ASTM-D3034 Standard Specification for PSM Polyvinyl Chloride Sewer Pipe, SDR-35 or equal, with "clean" 1/2 inch to 1 inch granular stone bedding uniformly graded. This bedding shall extend from 4 inches below the pipe to springline of pipe. Immediate backfill over pipe shall consist of same size "clean" or "minus" stone from springline of pipe to 6 inches above the
- 13. All sanitary and storm sewer trench backfills shall be water jetted. Granular backfill will be used under pavement areas.
- 14. All pipes shall have positive drainage through manholes. No flat invert
- 15. All creek crossings shall be grouted rip-rap as directed by District inspectors. (All grout shall be high slumpp ready-mix concrete).
- 16. Brick shall not be used on sanitary sewer manholes. 17. Existing sonitary sewer service shall not be interrupted.
- 18. Maintain access to existing residential driveways and streets.
- 19. Pre-manufactured adapters shall be used at all PVC to DIP connections. Rubber boot / Mission-type couplings will not be allowed.
- 20. Any permits, licenses, easements, or approvals required to work on public
- or private properties or roadways are the responsibility of the developer.
 - SEWER MAIN INSTALLATION ALWAYS KEEP THE SEWER MAIN ON EASEMENT
- Sewer mains are to be at least 8" PVC with a SDR35 rating.
- On new construction and sewer taps, as-built location of laterals must be provided to Duckett Creek.
- Final Testing: A Mondrel must be pulled through and an air test may be
- All trench backfill under paved areas shall be 3/4" minus granular backfill. water jetted, and all trench backfills may be earth material (free of large clads or stance, nothing over a 6" diameter) and shall be water jetted, inspected and approved
- 5. All drop sewer lines are to be ductile iron for the first 20', upstream from the
- 6. All drop manholes are to be 48", waterproofed. All double drop manholes are to be 60" water proofed.
- 42" manholes/Waterproofed are used for 8" sewers only. 48" manholes/Waterproofed are used for all sewer over 8".
- All sewer mains 20' or more in depth are to be C900PVC.


NOTE: 48 HOUR NOTICE REQUIRED ON ALL INSPECTIONS

CONSTRUCTION PLANS HIDDEN CREEK

PHASE 1

A TRACT OF LAND BEING ALL OF LOT 10 OF HOWELL'S PRAIRIE TRACT U.S. SURVEY 1669 ST. CHARLES COUNTY, MISSOURI





SUBDIVISION NOTES:

AREA OF PHASE 1 - 34.22 ACRES

NUMBER OF LOTS 62 SIDE YARD SETBACK 6'

Orive way locations shall not interfere with the sidewalk handicap ramps.

City approval of the construction Site plans does not mean that single family dwelling units can be constructed on the lots without meeting the building setbacks as required by the Zoning Code.

opproved MoDOT specifications.

All sign posts and backs and bracket arms shall be painted black using Carboline Rustbond Penetrating Sealer SG aand Carboline 133 HB paint (or equivalent as approved by the City and/or MaDOT)

The Contractor shall assume complete responsibility for controlling all siltation and erosion of the project area. The Contractor shall use whatever means necessary to control erosion and siltation including, but not limited to, staked straw bales and/or siltation control fences (possible methods of control are detailed on the interum grading plan). Control shall commence with grading and be maintained thughout the project until acceptance of the work by the Owner and/or City if O'Fallon and/or St. Charles County. The Contractor's responsibilities include all design and implementation as required to prevent erosion and depositing of silt. The Owner and/or the City of O'Falion and/or St. Charles County may at their aption direct the Contractor in his methods as deemed fit to protect property and improvements. Any depositing of slits or mud on new or existing pavement or in new or existing storm sewers or swales shall be removed after each rain and affected areas cleaned to the satisfaction of the Owner and/or the City of O'Fallon and/or St. Charles

PROPOSED FLOODPLAIN ARE PLOTTED ON THIS PLAN SET.

NOTE: ALL LOTS SHALL BE GRADED TO AN ELEVATION ABOVE THE 100-YEAR FLOODPLAIN.

Aluminum Olsk on the North Side of existing O'Fallon Road being 59'+ or - East of the Most Northern Corner of Property.

Site is served by:

Water Missouri American Water Duckett Creek Sewer District Telephone Southwestern Bell Telephone Electric Ameren UE St. Charles Gas Company Cottleville Fire Protection District

INDEX

	1	COVER SHEET
	2-3	FLAT PLAN
	4-5	GRADING PLAN
	6	STREET PROFILES
	7	ENTRANCE PLAN
	8	CUL - DE - SAC WARPIN
	9-10	SANITARY PROFILES
	11	STORM PROFILES
	12	OFF-SITE DETENTION
	13-14	DRAINAGE AREA MAP
	15-16	WATER LINE PLANS
1	17	LANDSCAPING
	D-1	PAVEMENT DETAILS
	D-2	SIDEWALK DETAILS
	D-3-D	-5 STORM DETAILS
	D-6-D	-7 SANITARY DETAILS
	D-8-D	-9 WATER DETAILS

MISC. DETAILS

ENGINEERS AUTHENTICATION

The responsibility for the professional engineering liability on this project is hereby

limited to the set of plans authenticated by the seal, signature and date hereunder attached. Responsibility is disclaimed for all other engineering plans involved in the

project and specifically excludes revisions after this date unless reauthenticated

LEGEND

C.O. CLEAN OUT

T.B.R. TO BE REMOVED

T.B.P. TO BE PROTECTED

T.B.A. TO BE ABANDONED

B.C. BASE OF CURB

T.C. TOP OF CURB

T.W. TOP OF WALL

U.I.P. USE IN PLACE

577 EXISTING CONTOUR

--- 578 --- PROPOSED CONTOUR

TREE LINE

SAN. SEWER (EXISTING)

- SAN, SEWER (PROPOSED)

STORM DRAIN (EXISTING)

STORM DRAIN (PROPOSED)

PHONE BOX

HYDRANT

STREET SIGN

STOP SIGN

CONCRETE PAVEMENT

JP IRON PIPE

U.N.O. UNLESS NOTED OTHERWISE

TYP. TYPICAL

T.B.R.&R. TO BE REMOVED & RELOCATED

SANITARY STRUCTURE

STORM STRUCTURE

TEST HOLE

POWER POLE

CURB INLET

D.C.J. DOUBLE CURB INLET

D.A.J. DOUBLE AREA INLET

E.D. ENERGY DISSIPATOR

C.I.P. CAST IRON PIPE

GUY WIRE

WATER METER

POST

E.P. END PIPE

LIGHT STANDARD

GRATE INLET (EXISTING)

AREA INLET (EXISTING)

FLARED END SECTION

R.C.P. REINFORCED CONCRETE PIPE

C.M.P. CORRUGATED METAL PIPE

POLYWNYL CHLORIDE

VITRIFIED CLAY PIPE

APPROX. DIRECTION OF WATER FLOW

8/13/03 File Copy

PLACED RIP-RAP W/UNDERLAIN FABRIC



ORDER NO. 02-0162

DATE PEC 03/21/03

O'Fallon File

Number 1002.02

TYPICAL RESIDENTIAL LOT DESIGN

PHASE ONE EXTENDS NORTH TO THE CENTER OF CROOKED CREEK

FRONT YARD SETBACK 25' REAR YARD SETBACK 25"

All street signs and traffic signals shall be colored black in accordance with the

FLOOD PLAIN: ACCORDING TO FLOOD INSURANCE RATE MAP (FIRM) PANEL NUMBER 29183C435 E, DATED AUGUST 2, 1996, THIS PLAT IS IN ZONE AE FLOODPLAIN. THE LIMITS OF THE FLOODWAY, EXISTING FLOODPLAIN, AND

Site Benchmark (On USGS Datum) - Elevation 485.66 - Iron Rod with

Francis Howell School District

Pipeline Explorer Pipeline

DEVELOPER

VANTAGE HOMES, INC. P.O. BOX 1270 ST. PETERS, MO 63376