



GENERAL NOTES:
1:12 SLOPE ON ALL CONCRETE CURB RAMP, PROVIDE A LANDING THE SAME WIDTH AS CURB RAMP AND 5' LONG ADJACENT TO CURB RAMP WITH MAXIMUM 2% SLOPE IN ANY DIRECTION.
PROVIDE 6" TYPE 1 AGGREGATE BASE UNDER CURB RAMP
TRUNCATED DOMES IN PUBLIC RIGHT OF WAY SHALL BE CONSTRUCTED USING RED PRE CAST TRUNCATED DOMES SUCH AS THOUGH MFR BY ARMOR TILE OR APPROVED EQUAL

McDonald's
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF McDONALD'S CORPORATION AND SHALL NOT BE COPIED OR REPRODUCED WITHOUT THEIR WRITTEN PERMISSION.

NO.	REV.	DATE	DESCRIPTION	UNITS OF MEASURE
1	1			
2	1			
3	1			
4	1			
5	1			
6	1			
7	1			
8	1			
9	1			
10	1			
11	1			
12	1			
13	1			
14	1			
15	1			
16	1			
17	1			

STATE OF MISSISSIPPI
REGISTERED PROFESSIONAL ENGINEER
ROBERT E. POLK
LICENSE NO. 20087
DATE 10-26-11

McDonald's CORPORATION SITE DETAILS
CURBS, WALKS, PAVEMENT MARKINGS AND SIGNS

DRAWN BY	CHECKED BY	DATE CHECKED	DATE APPROVED	DATE ISSUED
13ALG89				

DRAWING ID: 13ALG89
D:\WORK\BUILDINGS\SD SHEETS
PLOT: 1=1"

SHEET NO. **SD1**