



ADDITIONAL SANITARY SEWER NOTES FOR ST. CHARLES COUNTY
 ALL SANITARY LATERAL STREET CROSSINGS, IF TRENCHED, SHALL BE BACKFILLED WITH GRANULAR MATERIAL (AGGREGATE).
 STORM SEWER PIPES THAT CROSS OVER EXISTING OR PROPOSED SANITARY SEWER TRENCHES SHALL BE CRADLED IN CONCRETE THROUGH THE FULL WIDTH OF THE SANITARY SEWER TRENCH. THE TRENCH SHALL BE BACKFILLED AND COMPACTED WITH GRANULAR FILL TO THE BOTTOM OF THE CONCRETE CRADLE.
 CONTRACTOR MUST NOTIFY THE OWNERS OF THE PRIVATE PROPERTIES AFFECTED BY THE OFF-SITE SANITARY SEWER CONSTRUCTION A MINIMUM OF 48 HOURS BEFORE COMMENCING THE OFF-SITE IMPROVEMENTS.
 IF THE STORM AND SANITARY SEWER ARE PARALLEL AND IN THE SAME TRENCH OR OVERDIG, THE UPPER PIPE SHALL BE PLACED ON A SHELF AND THE LOWER PIPE SHALL BE BEDDED IN COMPACTED GRANULAR FILL TO THE FLOW LINE OF THE UPPER PIPE.

VERT. 1"=10'
 HORIZ. 1"=60'
 SCALE:

08/28/03	REVISED PER DCS COMMENTS
08/10/03	REVISED PER DCS COMMENTS
08/28/03	REVISED PER CITY OF DARDENNE PARK AND ST. CHARLES COUNTY COMMENTS

IMPROVEMENT PLANS
 PEACEFUL VALLEY
 SANITARY PROFILES 1

ST. CHARLES ENGINEERING & SURVEYING, INC.
 801 S. FIFTH STREET, SUITE 202
 ST. CHARLES, MO 63301
 TEL: (636) 947-0607 FAX: (636) 947-2448



ORDER NO.	02-0890
DATE	07/25/08
	5