



- 1. ALL PROPOSED UTILITIES AND/OR UTILITY RELOCATIONS SHALL BE LOCATED UNDERGROUND.
- 2. ALL SANITARY SEWER LATERALS AND SANITARY MAINS CROSSING UNDER PAVEMENT MUST HAVE PROPER ROCK
- 3. LIGHTING VALUES WILL BE REVIEWED ON SITE PRIOR TO THE FINAL OCCUPANCY INSPECTION.
- 4. PROVIDE A MARKING ON THE STORM SEWER INLETS. THE CITY WILL ALLOW THE FOLLOWING MARKERS AND ADHESIVE PROCEDURES ONLY AS SHOWN BELOW OR AN APPROVED EQUAL. 'PEEL AND STICK' ADHESIVE PADS WILL NOT BE

NO DUMPING DRAINS TO WATERWAYS (SD-W-CC) STANDARD STYLE NO DUMPING DRAINS TO STREAMS (#SDS)

- 5. EXISTING SANITARY SEWER SERVICE SHALL NOT BE INTERRUPTED.
- CONNECTIONS TO EXISTING SANITARY SEWER LATERAL REQUIRES NO DCSD INSPECTION. IF FOR ANY REASON THE EXISTING SANITARY SEWER LATERAL CANNOT BE USED AND A NEW CONNECTION TO THE SANITARY SEWERS IS NEEDED, DCSD INSPECTION WOULD BE REQUIRED. CONTACT STEVE OVERBEY, DCSD CHIEF INSPECTOR, AT 636-441-1244 TO SCHEDULE INSPECTION. 48 HOUR ADVANCE NOTICE IS REQUIRED.

SHOPPES AT WING
THE PET DOCTOR/YU
TECHNOLOGY DRIV
O'FALLON, MO 633

CHECKED BY

NOT TO SCALE

06/02/2016

16-0063

Sheet Number C6.0