Table 60-5 Soil Stabilization Schedule

Soil Disturbance Activity or Condition	Required Stabilization Time
Soil disturbance has ceased in areas greater than 2,000 square feet.	14 days
After construction of dikes, swales, diversions, and other concentrated flow areas	5 days
When slopes are steeper than 3 horizontal to 1 vertical	7 days
When slopes are greater than 3% and longer than 150 feet.	14 days
Perimeter controls around soil stockpiles.	End of workday
Stabilization or covering of inactive stockpiles.	30 days
When land disturbance is completed, permanent soil stabilization must be installed.	30 days

Table 60-6 Soil Amendment Rates

Soil Amendment Material		Application Rate (Lb per Acre)	
Fertilizer	Nitrogen (N)	30 1	
	Phosphate (P ₂ O ₅)	90 ¹	
	Potash (K ₂ O)	90 ¹	
Lime		1,000 2	

¹Increase the rate by 25% for slopes steeper than 5:1. ²Rate is in effective neutralizing material (ENM) units.

Table 60-7 Temporary Fall Seeding

Plant Species	Rate 1 (lb/acre)	Seeding Times
Side-Oats	65	8/16 - 9/30
Winter Rye	50	8/01 - 10/15
Winter Wheat	60	8/01 - 10/15
Orchard Grass	120	8/01 - 10/15
Perennial Ryegrass	80	8/01 - 10/15
Tall fescue, Smooth Brome	80	8/01 - 10/15
C-31 Fescue	120	9/01 - 11/15
Ladino Clover	2 2	8/15 - 9/15
Crimson Clover	6 ²	8/15 - 9/15
Orchard Grass and Dats or Rye	15 ² 40 ²	8/15 – 9/15

¹If using aerial seeding or other broadcast method to apply seed without rolling or cultipacking, increase seeding rates by 50 percent.

Table 60-9 Mulching Materials

Table 60-9 Mulching Materials					
Material	Rate	Requirements	Installation/Uses		
Straw	1.5-2.5 tons/ac (3-4 tons, if roller punched)	Dry, unchopped, unweathered; free of weed seeds & rot.	Spread by machine 1.5-2.5 inches deep; must be tacked or tied down.		
Compost Blanket	1" thick	Double the application rate for embankments	Follow manufacturer's application method.		
Wood fiber, wood cellulose, paper	1-2 tons/ac	Double the application rate in critical areas	Use with power mulcher or hydroseeder; may be used to tack straw on steep slopes. Cannot be used in hot dry weather.		

Architect: 210 South Market St., Suite B Troy, OH 45373 p 937.760.3884 mtwiss@gomtstudio.com


Civil Engineer: REYLING DESIGN & CONSULTING 4516 Boardwalk | Smithton, IL | 62285 reylingdc@gmail.com Missouri Firm License: 2016012969 MO Certificate of Authority: LC001485066

RDC Project No. 20-115



ENGINEER OF RECORD: Todd J. Reyling, PE

Missouri PE 2011020072



ISSUED / REVISED DATE REVISED PER CITY/MoDOT COMMENTS 07.20.2021 REVISED PER CITY/MoDOT COMMENTS 08.10.2021 REVISED PER CITY COMMENTS 12.01.2021

Civil Construction **Details**

²Pure live seed (PLS)