## Material

Soil creating foundation - Sand and Gravel - Foundation Soil **Basic soil parameters** 

No.	Name	Pattern	Φ <sub>ef</sub> [°]	c <sub>ef</sub> [psf]	γ [pcf]	Y <sub>su</sub> [pcf]	δ [°]
1	Lean Clay		29.00	25.0	120.00	58.50	19.00
2	Granular Backfill		39.00	0.0	135.00	72.50	28.00
3	Sand and Gravel - Foundation Soil		30.00	0.0	130.00	67.50	20.00

All soils are considered as cohesionless for at rest pressure analysis. **Soil parameters** 

## Lean Clay

Stress-state : effective	
Angle of internal friction : $\phi_{ef} = 29.00^{\circ}$	
Cohesion of soil : $c_{ef} = 25.0 \text{ ps}$	sf
Angle of friction strucsoil : $\delta = 19.00^{\circ}$	
Saturated unit weight : $\gamma_{sat} = 121.0 \text{ p}$	cf
Granular Backfill	
Unit weight : $\gamma = 135.0 \text{ p}$	cf
Stress-state : effective	
Angle of internal friction : $\phi_{ef}$ = 39.00 °	
Cohesion of soil : $c_{ef} = 0.0 p_{ef}$	sf
Angle of friction strucsoil : $\delta = 28.00^{\circ}$	
Saturated unit weight : $\gamma_{sat} = 135.0 \text{ p}$	cf

## Sand and Gravel - Foundation Soil

Unit weight :	γ =	130.0 pcf
Stress-state :	effectiv	e
Angle of internal friction :	$\varphi_{ef}$ =	30.00 °
Cohesion of soil :	c <sub>ef</sub> =	0.0 psf
Angle of friction strucsoil :	δ =	20.00 °
Saturated unit weight :	γ <sub>sat</sub> =	130.0 pcf

## Backfill

Backfill is not considered. Geological profile and assigned soils

No.	Thickness of layer t [ft]	Depth z [ft]	Assigned soil	Pattern
1	-	∞ 00.0	Lean Clay	

[Redi-Rock - Redi-Rock Wall + (32 bit) | version 5.2022.42.0 | Copyright © 2022 Fine spol. s r.o. All Rights Reserved | www.finesoftware.eu] [Redi-Rock International | (231) 237 - 9500 ext 3010| engineering@redi-rock.com| www.redi-rock.com]