

No.	Description	Height h [in]	Width w [in]	Unit weight γ [pcf]
4	Top block 24 straight	18.00	24.00	108.00
5	Planter 41	18.00	40.50	120.00
6	Planter 60	18.00	60.00	112.00
7	Top block 28	18.00	28.00	120.00
8	Top block 41	18.00	40.50	120.00
9	Top block 24 straight garden	18.00	24.00	80.00
10	Block R-5236 HC	36.00	52.00	110.00
11	Block R-7236 HC	36.00	72.00	110.00
12	Block R-9636 HC	36.00	96.00	110.00
13	Block R-41 HC	18.00	40.50	110.00

No.	Description	Min. shear strength F _{min} [lbf/ft]	Max. shear strength F _{max} [lbf/ft]	Friction f [°]
1	Block 28	6061.00	11276.00	44.00
2	Block 41	6061.00	11276.00	44.00
3	Block 60	6061.00	11276.00	44.00
4	Top block 24 straight	6061.00	11276.00	44.00
5	Planter 41	6061.00	11276.00	44.00
6	Planter 60	6061.00	11276.00	44.00
7	Top block 28	6061.00	11276.00	44.00
8	Top block 41	6061.00	11276.00	44.00
9	Top block 24 straight garden	6061.00	11276.00	44.00
10	Block R-5236 HC	4550.00	12000.00	44.00
11	Block R-7236 HC	4550.00	12000.00	44.00
12	Block R-9636 HC	4550.00	12000.00	44.00
13	Block R-41 HC	5358.00	12906.00	37.00

Setbacks

No.	Setback s [in]
1	0.010
2	0.375
3	1.625
4	9.375
5	16.625

Geometry

No. group	Description	Count	Setback s [in]
1	Block 60	1	1.62
2	Block 41	1	1.62
3	Block 28	2	1.62
4	Top block 28	1	-

Base

Geometry