



DOOR SCHEDULE:

NO.	DOOR SIZE	TYPE	FRAME	FINISH	NOTES
1	14 GA POLYURETHANE INSULATED STEEL DOOR R-2.5 WITH 22 GA STIFFENERS - PAINTED	HM-1			

DOOR TYPES FRAME TYPES
SCALE: 1/2" = 1'-0"

DOOR SCHEDULE NOTES:

- DOOR HARDWARE SHALL BE CAPABLE OF OPERATION WITH THE USE OF ONE (1) HAND AND SHALL NOT REQUIRE TIGHT FINISHING, TIGHT GRABBING OR TIGHT TURNING OF THE WREST TO OPERATE. THUMB TURN DEAD BOLTS ARE PROHIBITED. LEVER OR PADLOCK DEAD BOLT RELEASES ARE ACCEPTABLE. DOOR THRESHOLD SHALL NOT EXCEED ONE-HALF INCH (1/2") IN HEIGHT. THRESHOLDS EXCEEDING ONE-QUARTER INCH (1/4") IN HEIGHT SHALL HAVE A 1/2 BEVEL. DOOR CLOSERS SHALL MEET OPENING FORCE AND SUEEP PERIOD REQUIREMENTS.
- ALL HARDWARE SHALL COMPLY WITH THE STATE OF MISSOURI ACCESSIBILITY CODE, LATEST EDITION.

DOOR HARDWARE GROUPS:

GROUP	ITEM	DESCRIPTION	QTY	UNIT	FINISH
GROUP 1	1	HINGE	48	EA	630
	2	EXIT DEVICE	48	EA	630
	3	EXIT DEVICE TRIM	48	EA	630
	4	CYLINDER	48	EA	630
	5	CLOSER	48	EA	630
	6	KICKPLATE	48	EA	630
	7	THRESHOLD	48	EA	630
	8	SWEEP	48	EA	630
	9	LEATHERSTRIP	48	EA	630
	10	DRIP GUARD	48	EA	630

