

PAVEMENT MARKING LEGEND

WATERBORNE PAVEMENT MARKING PAINT W/TYPE P BEADS:
 SW = SOLID WHITE
 DW = DOTTED WHITE (2' STRIPE, 4' GAP)
 SY = SOLID YELLOW
 IY = INTERMITTENT YELLOW (10' STRIPE, 30' GAP)
 DSY = DOUBLE SOLID YELLOW

PERFORMED THERMOPLASTIC:
 SWT = SOLID WHITE
 DWT = DOTTED WHITE (2' STRIPE, 4' GAP)


↔ = LEFT/RIGHT ARROW
 = YIELD LINE TRIANGLES

NOTES:


BLACK CONTRAST MARKINGS ARE REQUIRED FOR ALL LANE LINES ON CONCRETE PAVEMENT (NO DIRECT PAY).

ALL STOP AND YIELD BARS SHALL BE A MINIMUM OF 4' FROM CROSSWALK MARKINGS UNLESS SPECIFIED OTHERWISE.


ALL LANE LINES SHALL BE WATERBORNE PAVEMENT MARKING PAINT WITH TYPE "P" BEADS.




DATE PREPARED 8/14/2024	
DISTRICT S1	STATE MO
SHEET NO. 46	
ROUTE WELDON SPRING	
DA JOB NO. 221150	
EW GATEWAY ID. 7209-22	
PROJECT NO. CMAQ-7302(691)	
BRIDGE NO. N/A	
DATE	DESCRIPTION



OATES
BLAIR, MO 64801
315-274-1415
MISSOURI RESIDENT
LICENSE NO. 001181



MISSOURI STATE REVIEW CORP
LICENSE NO. 000276



CITY OF FALLON
100 NORTH MAIN STREET
FALLON, MO 64306
Tel: 886-219-5996

PAVEMENT MARKING PLAN
SHEET 1 OF 2

REV.