



B-85A/B/S
MEMBRANE AERATION BLOWERS
INITIAL FLOW: 689 SCFM @ 4.25 PSIG
MAX. FLOW: 878 SCFM @ 4.54 PSIG
30 HP, 3600 RPM
460 V / 3 Ph / 60 Hz

- NOTES:
1. ALL DOTTED LINES/EQUIPMENT BY OTHERS
 2. THE ACTUAL BLOWER DISCHARGE PRESSURE DETERMINED BASED ON MAXIMUM POSSIBLE LIQUID LEVEL IN MEMBRANE TANKS.
 3. ALL VALUES ARE PRELIMINARY.

ZENON Environmental Inc.
Oakville, Ontario 905-465-9030

DEC 23 2004

ISSUED FOR APPROVAL

By *[Signature]*

0	04/12/22	ISSUED FOR APPROVAL		L.S.	D.Z.
REV.	DATE	DESCRIPTION	ZONE	DSGN	APPD
APPROVAL	DATE	<p>ZENON Environmental Inc. 223 - OAKVILLE ONTARIO</p> <p>CUSTOMER: DD HIGHWAY, MO</p> <p>TITLE: PIPING & INSTRUMENTATION DIAGRAM MEMBRANE AERATION BLOWERS</p>			
DRWN: E.D.	04/09/21				
DSGN: A.C.	04/09/21				
CHKD: A.C.	04/12/15				
APPD: D.Z.	04/12/15				
CADD FILE:	50029202 1.DGN				
SCALE:	1:1	SIZE: D	DRAWING NO: 500292-D-002	SHEET 1 OF 2	REV. 0