



ENGINEERING

PLANNING

SURVEYING

**STORMWATER DETENTION ANALYSIS**  
**MANDERLEY ESTATES - O'FALLON**  
**PREPARED BY: BAX ENGINEERING CO., INC.**  
**BAX PROJECT NO. 96-8169**  
**NOVEMBER 15, 1996**  
**REVISED DECEMBER 11, 1996**  
**REVISED FEBRUARY 6, 1997**

INTRODUCTION:

The tract of land is presently an undeveloped site located in the City of O'Fallon, Missouri. It is proposed that the tract, consisting of 52.50 acres, be developed into a single family residential subdivision. An existing lake and stormwater detention basin near the Northeast corner of the site will provide detention for the development, along with detention for Lone Star Industrial Park which consists of 105.76 Acres, as required by the City of O'Fallon. The storage volume and outflow rates shall be proportioned to insure that the peak rate of runoff leaving the site under post-developed conditions is less than or equal to the peak rate of runoff leaving the site under pre-developed conditions for the required design storms. The basin shall be analyzed for both the 15 year frequency - 20 minute and the 25 year frequency - 20 minute duration design storms. The 100 year frequency - 20 minute design storm will be checked for safe passage.

GENERAL SITE DATA AND RUNOFF CALCULATIONS:

Site area: 52.50 Acres

The pre-developed P.I. factors to be used for analysis are:

- ONSITE: 15 year - 20 minute storm (assumed 5% impervious): 1.87 c.f.s./Ac
- LONE STAR IND. PARK: 15 year - 20 minute storm (assumed 5% impervious): 1.87 c.f.s./Ac
- OFFSITE: 15 year - 20 minute storm (assumed 40% impervious): 2.64 c.f.s./Ac.
- OFFSITE: 15 year - 20 minutes storm (assumed 100% impervious): 3.85 c.f.s./Ac.

The post-developed P.I. factors to be used for analysis are:

- ONSITE: 15 year - 20 minute storm (developed single family): 2.09 c.f.s./Ac
- LONE STAR IND. PARK: 15 year - 20 minute storm (developed heavy industrial): 3.85 c.f.s./Ac
- OFFSITE: 15 year - 20 minute storm (assumed 40% impervious): 2.64 c.f.s./Ac.
- OFFSITE: 15 year - 20 minute storm (assumed 100% impervious): 3.85 c.f.s./Ac.

BAX ENGINEERING CO., INC.  
 1052 South Cloverleaf Drive  
 St. Peters, MO 63376-6445  
 314-928-5552 FAX 928-1718



ENGINEERING

PLANNING

SURVEYING

The pre-developed P.I. factors to be used for analysis are:

ONSITE: 25 year - 20 minute storm (assumed 5% impervious): 2.31 c.f.s./Ac  
LONE STAR IND. PARK: 25 year - 20 minute storm (assumed 5% impervious): 2.31 c.f.s./Ac  
OFFSITE: 25 year - 20 minute storm (assumed 40% impervious): 3.26 c.f.s./Ac.  
OFFSITE: 25 year - 20 minutes storm (assumed 100% impervious): 4.75 c.f.s./Ac.

The post-developed P.I. factors to be used for analysis are:

ONSITE: 25 year - 20 minute storm (developed single family): 2.58 c.f.s./Ac  
LONE STAR IND. PARK: 25 year - 20 minute storm (developed heavy industrial): 4.75 c.f.s./Ac  
OFFSITE: 25 year - 20 minute storm (assumed 40% impervious): 3.26 c.f.s./Ac.  
OFFSITE: 25 year - 20 minute storm (assumed 100% impervious): 4.75 c.f.s./Ac.

#### TIME OF CONCENTRATION:

Of the inflows to the basin, the most remote point of origination lies offsite to the Southwest. It will flow approximately 1,400 feet over pavement, then an additional 1,300 feet overland, then an additional 200 feet via storm sewer and then another 335 feet overland to the detention basin. Time of concentration is estimated as follows:

T(pavement): L = 1,400 feet  
Elevation difference = 580 - 520 = 60 feet  
T(pavement) = 2.80 minutes: See Figure 1

T(overland): L = 1,300 feet  
Elevation difference = 520 - 480 = 40 feet  
T(overland) = 7.5 minutes: See Figure 1

T(stormpipe): L = 200 feet  
Estimated velocity 7 feet/second  
T(stormpipe) =  $\frac{200 \text{ feet}}{7 \text{ feet/sec}}$   
= 28.57 seconds = 0.48 minutes

T(overland): L = 335 feet  
Elevation difference = 476 - 468.5 = 7.5 feet  
T(overland) = 2.85 minutes: See Figure 1

Total Time: T(overland) + T(storm pipe) + T(overland) + T(pavement)  
= 2.85 min. + 0.48 min. + 7.50 min. + 2.80 min. = 13.63 min. => use 13.0 minutes



ENGINEERING

PLANNING

SURVEYING

REQUIRED ATTENUATION

Tract Area x [PI(post) - PI(pre)]

15 year - 20 minutes storm

On-site = 52.50 x (2.09 - 1.87) = 11.55 c.f.s.

+ 83.26 - 52.50 = 30.76 (3.85 - 1.87)  
= 60.90

Lone Star Industrial Park = 105.76 x (3.85 - 1.87) = 209.40 c.f.s.

Total 220.95 c.f.s.

↳ 281.85

BASIN PEAK INFLOW

Inflows to the basin have been estimated from the drainage area map of the project. (See Construction Plans)

PRE-DEVELOPED RUNOFF (15 year - 20 minute storm)

Flow going to the basin:

On-site areas (assumed 5% impervious)

15 year - 20 minute storm  $Q_{pre}$  = 30.19 acres @ 1.87 = 56.46 c.f.s.

Lone Star Industrial Park areas (assumed 5% impervious)

15 year - 20 minute storm  $Q_{pre}$  = 51.81 acres @ 1.87 = 96.88 c.f.s.

Off-site areas (assumed 100% impervious)

15 year - 20 minute storm  $Q_{pre}$  = 49.19 acres @ 3.85 = 189.38 c.f.s.

Off-site areas (assumed 40% impervious)

15 year - 20 minute storm  $Q_{pre}$  = 11.43 acres @ 2.64 = 30.18 c.f.s.

Total 372.90 c.f.s.

100 year - 20 minute storm = 15 year - 20 minute storm x 1.58  
= 372.90 c.f.s. x 1.58 = 589.18 c.f.s.

Flow Bypassing the Basin:

On-site areas (assumed 5% impervious)

15 year - 20 minute storm  $Q_{pre}$  = 22.28 acres @ 1.87 = 41.66 c.f.s.



ENGINEERING

PLANNING

SURVEYING

Lone Star Industrial Park areas (assumed 5% impervious)

15 year - 20 minute storm  $Q_{pre} = 53.95 \text{ acres @ } 1.87 = 100.89 \text{ c.f.s.}$

Off-site areas (assumed 40% impervious)

15 year - 20 minute storm  $Q_{pre} = 27.0 \text{ acres @ } 2.64 = 71.28 \text{ c.f.s.}$

Total 213.83 c.f.s.

100 year - 20 minute storm = 15 year - 20 minute storm x 1.58  
= 213.83 c.f.s. x 1.58 = 337.85 c.f.s.

POST-DEVELOPED RUNOFF (15 year - 20 minute storm)

Flow going to the Basin:

On-site areas (assumed 15% impervious)

15 year - 20 minute storm  $Q_{post} = 30.19 \text{ acres @ } 2.09 = 63.10 \text{ c.f.s.}$

Lone Star Industrial Park (assumed 100% impervious)

15 year - 20 minute storm  $Q_{post} = 51.81 \text{ acres @ } 3.85 = 199.47 \text{ c.f.s.}$

Off-site areas (assumed 100% impervious)

15 year - 20 minute storm  $Q_{post} = 49.19 \text{ acres @ } 3.85 = 189.38 \text{ c.f.s.}$

Off-site areas (assumed 40% impervious)

15 year - 20 minute storm  $Q_{post} = 11.43 \text{ acres @ } 2.64 = 30.18 \text{ c.f.s.}$

Total 482.13 c.f.s.

100 year - 20 minute storm = 15 year - 20 minute storm x 1.58

= 482.13 c.f.s. x 1.58 = 761.77 c.f.s.

Flow Bypassing the Basin:

On-site areas (assumed 15% impervious)

15 year - 20 minute storm  $Q_{post} = 22.28 \text{ acres @ } 2.09 = 46.57 \text{ c.f.s.}$

Lone Star Industrial Park areas (assumed 100% impervious)

15 year - 20 minute storm  $Q_{post} = 53.95 \text{ acres @ } 3.85 = 207.71 \text{ c.f.s.}$



ENGINEERING

PLANNING

SURVEYING

Off-site areas (assumed 40% impervious)  
 15 year - 20 minute storm  $Q_{post} = 27.0 \text{ acres} @ 2.64 = 71.28 \text{ c.f.s.}$

Total 325.56 c.f.s.

100 year - 20 minute storm = 15 year - 20 minute storm x 1.58  
 = 325.56 c.f.s. x 1.58 = 514.38 c.f.s.

PERMITTED RELEASE RATE

The permitted release rate of the detention basin is found by subtracting the total required attenuation from the post-developed peak inflow to the basin for the design storm.

15 year - 20 minute storm  $281.85 = 200.28$   
 Permitted release rate = 482.13 c.f.s. - 220.95 c.f.s.  
 = 261.18 c.f.s.

ROUTING CALCULATIONS AND RESULTS

A computer program "Pondpack" was utilized in routing the design storms through the basin. As found in the routing calculations, the results of each analysis are as follows:

15 year - 20 minute storm:  
 Peak release rate = 33.43 (< 261.18 c.f.s.)  
 Peak elevation = 470.70

REQUIRED ATTENUATION

Tract Area x [PI(post) - PI(pre)]

25 year - 20 minutes storm

On-site = 52.50 x (2.58 - 2.31) = 14.18 c.f.s.

$+ 30.76 (4.75 - 2.31) = 75.05$

Lone Star Industrial Park = 105.76 x (4.75 - 2.31) = 258.05 c.f.s.

Total 272.23 c.f.s.  
347.28

BASIN PEAK INFLOW

Inflows to the basin have been estimated from the drainage area map of the project. (See Construction Plans)



ENGINEERING

PLANNING

SURVEYING

**PRE-DEVELOPED RUNOFF (25 year - 20 minute storm)**

Flow going to the basin:

On-site areas (assumed 5% impervious)

$$25 \text{ year - 20 minute storm } Q_{pre} = 30.19 \text{ acres @ } 2.31 = 69.74 \text{ c.f.s.}$$

Lone Star Industrial Park areas (assumed 5% impervious)

$$25 \text{ year - 20 minute storm } Q_{pre} = 51.81 \text{ acres @ } 2.31 = 119.68 \text{ c.f.s.}$$

Off-site areas (assumed 100% impervious)

$$25 \text{ year - 20 minute storm } Q_{pre} = 49.19 \text{ acres @ } 4.75 = 233.65 \text{ c.f.s.}$$

Off-site areas (assumed 40% impervious)

$$25 \text{ year - 20 minute storm } Q_{pre} = 11.43 \text{ acres @ } 3.26 = 37.26 \text{ c.f.s.}$$

Total 460.33 c.f.s.

$$\begin{aligned} 100 \text{ year - 20 minute storm} &= 25 \text{ year - 20 minute storm} \times 1.28 \\ &= 460.33 \text{ c.f.s.} \times 1.28 = 589.22 \text{ c.f.s.} \end{aligned}$$

Flow Bypassing the Basin:

On-site areas (assumed 5% impervious)

$$25 \text{ year - 20 minute storm } Q_{pre} = 22.28 \text{ acres @ } 2.31 = 51.47 \text{ c.f.s.}$$

Lone Star Industrial Park areas (assumed 5% impervious)

$$25 \text{ year - 20 minute storm } Q_{pre} = 53.95 \text{ acres @ } 2.31 = 124.62 \text{ c.f.s.}$$

Off-site areas (assumed 40% impervious)

$$25 \text{ year - 20 minute storm } Q_{pre} = 27.0 \text{ acres @ } 3.26 = 88.02 \text{ c.f.s.}$$

Total 264.11 c.f.s.

$$\begin{aligned} 100 \text{ year - 20 minute storm} &= 25 \text{ year - 20 minute storm} \times 1.28 \\ &= 264.11 \text{ c.f.s.} \times 1.28 = 338.06 \text{ c.f.s.} \end{aligned}$$

**POST-DEVELOPED RUNOFF (25 year - 20 minute storm)**

Flow going to the Basin:

On-site areas (assumed 15% impervious)

$$25 \text{ year - 20 minute storm } Q_{post} = 30.19 \text{ acres @ } 2.58 = 77.89 \text{ c.f.s.}$$



ENGINEERING

PLANNING

SURVEYING

Lone Star Industrial Park (assumed 100% impervious)  
25 year - 20 minute storm  $Q_{post} = 51.81 \text{ acres @ } 4.75 = 246.10 \text{ c.f.s.}$

Off-site areas (assumed 100% impervious)  
25 year - 20 minute storm  $Q_{post} = 49.19 \text{ acres @ } 4.75 = 233.65 \text{ c.f.s.}$

Off-site areas (assumed 40% impervious)  
25 year - 20 minute storm  $Q_{post} = 11.43 \text{ acres @ } 3.26 = 37.26 \text{ c.f.s.}$

Total 594.90 c.f.s.

100 year - 20 minute storm = 25 year - 20 minute storm x 1.28  
= 594.90 c.f.s. x 1.28 = 761.47 c.f.s.

Flow Bypassing the Basin:

On-site areas (assumed 15% impervious)  
25 year - 20 minute storm  $Q_{post} = 22.28 \text{ acres @ } 2.58 = 57.48 \text{ c.f.s.}$

Lone Star Industrial Park areas (assumed 100% impervious)  
25 year - 20 minute storm  $Q_{post} = 53.95 \text{ acres @ } 4.75 = 256.26 \text{ c.f.s.}$

Off-site areas (assumed 40% impervious)  
25 year - 20 minute storm  $Q_{post} = 27.0 \text{ acres @ } 3.26 = 88.02 \text{ c.f.s.}$

Total 401.76 c.f.s.

100 year - 20 minute storm = 25 year - 20 minute storm x 1.28  
= 401.76 c.f.s. x 1.28 = 514.25 c.f.s.

PERMITTED RELEASE RATE

The permitted release rate of the detention basin is found by subtracting the total required attenuation from the post-developed peak inflow to the basin for the design storm.

25 year - 20 minute storm - 347.28 = 247.62  
Permitted release rate = 594.90 c.f.s. - 272.23 c.f.s.  
= 322.67 c.f.s.



ENGINEERING

PLANNING

SURVEYING

## ROUTING CALCULATIONS AND RESULTS

A computer program "Pondpack" was utilized in routing the design storms through the basin. As found in the routing calculations, the results of each analysis are as follows:

25 year - 20 minute storm:

Peak release rate = 42.37 (< 322.67 c.f.s.)

Peak elevation = 471.31

\*100 year - 20 minute storm: (worst case)

Weir Elevation = 471.50

$Q = CLH^{1.5}$

$Q = 761.77$  c.f.s.

$C = 3.0$

$L = 46.0$  feet

$H = 3.20$  feet

Elev. = 474.70

Freeboard = 476.00 - 474.70 = 1.30 feet

Check

$Q = 3.0 (46.0)(3.20)^{1.5}$

$Q = 789.96$  c.f.s.

789.96 c.f.s. > 761.77 c.f.s.

## CHECKING DISCHARGE PIPES

100 year - 20 minute storm: (see Page 10)

$Q = 761.77$  c.f.s.

Existing Discharge Pipes: 2-72" CMP

Flowline of Existing Pipes: 462.50

Check under inlet control

$HW/D = 1.7 \Rightarrow 1.7 \times 72" = 10.2$  feet

Elevation = 462.50 + 10.2 = 472.70 Controls

## DETENTION BASIN CHARACTERISTICS SUMMARY:

15 year - 20 minute storm highwater = 470.70

25 year - 20 minute storm highwater = 471.31

100 year - 20 minute storm highwater = 474.70





*ENGINEERING*

*PLANNING*

*SURVEYING*

Overflow Structure:

Existing concrete structure with grate inlet top

Flowline of the two existing 72" CMP = 462.50

Flowline of low flow slot - (13.2" w x 30" h) = 467.75

Flowline of emergency overflow = 471.50

\*Note: The 100 year - 20 minute storm was checked for safe passage through the basin in a worst case situation with the low flow opening blocked.



Project: WANDERLEY PLACE

Date: 2-6-97 Project No: 96-0169

Designed: MRK Checked: \_\_\_\_\_

CHART 2

D = 2 Existing 72" CMP


TQ = 761.77 cfs.

$\frac{TQ}{2} = 380.89$  cfs.

D = 72"

K = 462.50

H<sub>w</sub> + K = 472.50



$\frac{H_w}{D} = 1.7$   
 $H_w = 1.7(6)$   
 = 10.20

HEADWATER DEPTH FOR CONCRETE PIPE CULVERTS WITH INLET CONTROL

HEADWATER SCALES 2 & 3  
 REVISED MAY 1964

BUREAU OF PUBLIC ROADS JAN. 1963





FIGURE 1

TIME OF CONCENTRATION OF SMALL DRAINAGE BASINS



526

Disposal

HOFF ROAD

Peruque

WT

Pit

2 LANE

70

70

573

560

580

584 X

500

500

567

586

500

550

009

558

553

552

551

550

549

548

547

546

545

544

543

542

541

540

539

538

537

536

535

534

533

532

531

530

529

528

527

526

525

524

523

522

521

520

519

518

517

516

515

514

513

512

511

510

509

508

507

506

505

504

503

502

501

500

499

498

497

496

495

494

493

492

491

490

489

488

487

486

485

484

483

482

481

480

479

478

477

476

475

474

473

472

471

470

469

468

467

466

465

464

463

462

461

460

459

458

457

456

455

454

453

452

451

450

449

448

447

446

445

444

443

442

441

440

439

438

437

436

435

434

433

432

431

430

429

428

427

426

425

424

423

422

421

420

419

418

417

416

415

414

413

412

411

410

409

408

407

406

405

404

403

402

401

400

399

398

397

396

395

394

393

392

391

390

389

388

387

386

385

384

383

382

381

380

379

378

377

376

375

374

373

372

371

370

369

368

367

366

365

364

363

362

361

360

359

358

357

356

355

354

353

352

351

350

349

348

347

346

345

344

343

342

341

340

339

338

337

336

335

334

333

332

331

330

329

328

327

326

325

324

323

322

321

320

319

318

317

316

315

314

313

312

311

310

309

308

307

306

305

304

303

302

301

300

299

298

297

296

295

294

293

292

291

290

289

288

287

286

285

284

283

282

281

280

279

278

277

276

275

274

273

272

271

270

269

268

267

266

265

264

263

262

261

260

259

258

257

256

255

254

253

252

251

250

249

248

247

246

245

244

243

242

241

240

239

238

Hydrograph file: 8169-15 .HYD

HYDROGRAPH ORDINATES (cfs)  
Time increment = 1.00 Minutes

Time on left represents time for first Q in each row.

Time Minutes	Time on left represents time for first Q in each row.						
0.00	0.00	37.09	74.17	111.26	148.35	185.44	222.52
7.00	259.61	296.70	333.78	370.87	407.96	445.04	482.13
14.00	482.13	482.13	482.13	482.13	482.13	482.13	482.13
21.00	445.04	407.96	370.87	333.78	296.70	259.61	222.52
28.00	185.44	148.35	111.26	74.17	37.09	0.00	

```

*****
*
*           MANDERLEY ESTATES           *
*           DETENTION ANALYSIS         *
*   PREPARED BY: BAX ENGINEERING CO., INC. *
*           FEBRUARY 06, 1997         *
*
*****
  
```

Inflow Hydrograph: 8169-15 .HYD  
 Rating Table file: 8169 .PND

----INITIAL CONDITIONS----

Elevation = 467.75 ft  
 Outflow = 0.00 cfs  
 Storage = 0.00 ac-ft

GIVEN POND DATA

ELEVATION (ft)	OUTFLOW (cfs)	STORAGE (ac-ft)
467.75	0.0	0.000
468.25	2.3	2.024
468.75	6.6	4.092
469.25	12.1	6.205
469.75	18.7	8.364
470.25	26.1	10.573
470.75	34.3	12.858
471.25	39.7	15.224
471.75	61.2	17.674
472.25	137.4	20.210
472.75	244.1	22.840
473.25	374.1	25.567
473.75	523.5	28.393
474.25	690.0	31.320
474.75	872.0	34.354
475.25	1068.3	37.497
475.75	1277.9	40.751

INTERMEDIATE ROUTING  
 COMPUTATIONS

2S/t (cfs)	2S/t + 0 (cfs)
0.0	0.0
2938.7	2941.0
5941.8	5948.4
9010.2	9022.3
12144.5	12163.2
15351.5	15377.6
18669.1	18703.4
22105.7	22145.4
25663.1	25724.3
29345.2	29482.6
33164.0	33408.1
37123.6	37497.7
41226.5	41750.0
45476.3	46166.3
49881.3	50753.3
54445.1	55513.4
59170.7	60448.6

Time increment (t) = 1.0 min.

POND-2 Version: 5.17 S/N:  
 EXECUTED: 02-06-1997 13:08:23

Pond File: 8169 .PND  
 Inflow Hydrograph: 8169-15 .HYD  
 Outflow Hydrograph: OUT .HYD

## INFLOW HYDROGRAPH

## ROUTING COMPUTATIONS

TIME (min)	INFLOW (cfs)	I1+I2 (cfs)	2S/t - 0 (cfs)	2S/t + 0 (cfs)	OUTFLOW (cfs)	ELEVATION (ft)
0.0	0.00		0.0	0.0	0.00	467.75
1.0	37.09	37.1	37.0	37.1	0.03	467.76
2.0	74.17	111.3	148.1	148.3	0.12	467.78
3.0	111.26	185.4	333.0	333.5	0.26	467.81
4.0	148.35	259.6	591.7	592.6	0.46	467.85
5.0	185.44	333.8	924.0	925.4	0.72	467.91
6.0	222.52	408.0	1329.9	1332.0	1.04	467.98
7.0	259.61	482.1	1809.2	1812.0	1.42	468.06
8.0	296.70	556.3	2361.8	2365.5	1.85	468.15
9.0	333.78	630.5	2987.5	2992.3	2.37	468.26
10.0	370.87	704.7	3685.4	3692.2	3.37	468.37
11.0	407.96	778.8	4455.3	4464.2	4.48	468.50
12.0	445.04	853.0	5296.9	5308.3	5.68	468.64
13.0	482.13	927.2	6209.9	6224.1	7.09	468.79
14.0	482.13	964.3	7156.6	7174.2	8.79	468.95
15.0	482.13	964.3	8099.9	8120.8	10.49	469.10
16.0	482.13	964.3	9039.7	9064.1	12.19	469.26
17.0	482.13	964.3	9975.7	10004.0	14.16	469.41
18.0	482.13	964.3	10907.7	10939.9	16.13	469.56
19.0	482.13	964.3	11835.8	11871.9	18.09	469.70
20.0	482.13	964.3	12759.7	12800.0	20.17	469.85
21.0	445.04	927.2	13642.4	13686.9	22.21	469.99
22.0	407.96	853.0	14447.3	14495.4	24.07	470.11
23.0	370.87	778.8	15174.6	15226.1	25.75	470.23
24.0	333.78	704.7	15824.6	15879.3	27.34	470.33
25.0	296.70	630.5	16397.6	16455.1	28.76	470.41
26.0	259.61	556.3	16893.9	16953.9	29.99	470.49
27.0	222.52	482.1	17314.0	17376.0	31.03	470.55
28.0	185.44	408.0	17658.2	17721.9	31.88	470.60
29.0	148.35	333.8	17926.9	17992.0	32.55	470.64
30.0	111.26	259.6	18120.4	18186.5	33.03	470.67
31.0	74.17	185.4	18239.2	18305.9	33.32	470.69
32.0	37.09	111.3	18283.6	18350.5	33.43	470.70
33.0	0.00	37.1	18254.0	18320.7	33.36	470.69

\*\*\*\*\* SUMMARY OF ROUTING COMPUTATIONS \*\*\*\*\*

Pond File: 8169 .PND  
Inflow Hydrograph: 8169-15 .HYD  
Outflow Hydrograph: OUT .HYD

Starting Pond W.S. Elevation = 467.75 ft

\*\*\*\*\* Summary of Peak Outflow and Peak Elevation \*\*\*\*\*

Peak Inflow = 482.13 cfs  
Peak Outflow = 33.43 cfs  
Peak Elevation = 470.70 ft

\*\*\*\*\* Summary of Approximate Peak Storage \*\*\*\*\*

Initial Storage = 0.00 ac-ft  
Peak Storage From Storm = 12.62 ac-ft  
-----  
Total Storage in Pond = 12.62 ac-ft




POND-2 Version: 5.17 S/N:

Pond File: 8169 .PND  
 Inflow Hydrograph: 8169-15 .HYD  
 Outflow Hydrograph: OUT .HYD

EXECUTED: 02-06-1997  
 13:08:23

Peak Inflow = 482.13 cfs  
 Peak Outflow = 33.43 cfs  
 Peak Elevation = 470.70 ft



x File: 8169-15 .HYD Qmax = 33.4 cfs  
 \* File: OUT .HYD Qmax = 482.1 cfs

>>>> HYDROGRAPH PRINTOUT <<<<<

02-06-1997 13:05:48

Hydrograph file: 8169-25 .HYD

HYDROGRAPH ORDINATES (cfs)

Time increment = 1.00 Minutes

Time  
Minutes

Time on left represents time for first Q in each row.

Time Minutes	0.00	7.00	14.00	21.00	28.00	35.00	42.00	49.00
0.00	0.00	320.33	594.90	549.13	228.80	183.04	137.28	91.52
7.00	0.00	320.33	594.90	549.13	228.80	183.04	137.28	91.52
14.00	0.00	320.33	594.90	549.13	228.80	183.04	137.28	91.52
21.00	0.00	320.33	594.90	549.13	228.80	183.04	137.28	91.52
28.00	0.00	320.33	594.90	549.13	228.80	183.04	137.28	91.52

```

*****
*
*           MANDERLEY ESTATES           *
*           DETENTION ANALYSIS         *
*   PREPARED BY: BAX ENGINEERING CO.. INC. *
*           FEBRUARY 06. 1997         *
*
*****
    
```

Inflow Hydrograph: 8169-25 .HYD  
 Rating Table file: 8169 .PND

----INITIAL CONDITIONS----  
 Elevation = 467.75 ft  
 Outflow = 0.00 cfs  
 Storage = 0.00 ac-ft

GIVEN POND DATA

ELEVATION (ft)	OUTFLOW (cfs)	STORAGE (ac-ft)
467.75	0.0	0.000
468.25	2.3	2.024
468.75	6.6	4.092
469.25	12.1	6.205
469.75	18.7	8.364
470.25	26.1	10.573
470.75	34.3	12.858
471.25	39.7	15.224
471.75	61.2	17.674
472.25	137.4	20.210
472.75	244.1	22.840
473.25	374.1	25.567
473.75	523.5	28.393
474.25	690.0	31.320
474.75	872.0	34.354
475.25	1068.3	37.497
475.75	1277.9	40.751

INTERMEDIATE ROUTING  
 COMPUTATIONS

2S/t (cfs)	2S/t + 0 (cfs)
0.0	0.0
2938.7	2941.0
5941.8	5948.4
9010.2	9022.3
12144.5	12163.2
15351.5	15377.6
18669.1	18703.4
22105.7	22145.4
25663.1	25724.3
29345.2	29482.6
33164.0	33408.1
37123.6	37497.7
41226.5	41750.0
45476.3	46166.3
49881.3	50753.3
54445.1	55513.4
59170.7	60448.6

Time increment (t) = 1.0 min.

POND-2 Version: 5.17 S/N:  
 EXECUTED: 02-06-1997 13:09:06

Pond File: 8169 .PND  
 Inflow Hydrograph: 8169-25 .HYD  
 Outflow Hydrograph: OUT .HYD

INFLOW HYDROGRAPH

ROUTING COMPUTATIONS

TIME (min)	INFLOW (cfs)	I1+I2 (cfs)	2S/t - 0 (cfs)	2S/t + 0 (cfs)	OUTFLOW (cfs)	ELEVATION (ft)
0.0	0.00		0.0	0.0	0.00	467.75
1.0	45.76	45.8	45.7	45.8	0.04	467.76
2.0	91.52	137.3	182.7	183.0	0.14	467.78
3.0	137.28	228.8	410.8	411.5	0.32	467.82
4.0	183.04	320.3	730.0	731.2	0.57	467.87
5.0	228.80	411.8	1140.1	1141.9	0.89	467.94
6.0	274.56	503.4	1640.9	1643.4	1.29	468.03
7.0	320.33	594.9	2232.3	2235.7	1.75	468.13
8.0	366.09	686.4	2914.1	2918.7	2.28	468.25
9.0	411.85	777.9	3685.3	3692.0	3.37	468.37
10.0	457.59	869.4	4545.5	4554.7	4.61	468.52
11.0	503.37	961.0	5494.5	5506.5	5.97	468.68
12.0	549.13	1052.5	6531.7	6547.0	7.67	468.85
13.0	594.90	1144.0	7656.4	7675.7	9.69	469.03
14.0	594.90	1189.8	8822.6	8846.2	11.78	469.22
15.0	594.90	1189.8	9984.0	10012.4	14.18	469.41
16.0	594.90	1189.8	11140.6	11173.8	16.62	469.59
17.0	594.90	1189.8	12292.2	12330.4	19.08	469.78
18.0	594.90	1189.8	13438.5	13482.0	21.74	469.96
19.0	594.90	1189.8	14579.6	14628.3	24.38	470.13
20.0	594.90	1189.8	15715.3	15769.4	27.07	470.31
21.0	549.13	1144.0	16799.8	16859.3	29.75	470.47
22.0	503.37	1052.5	17787.9	17852.3	32.20	470.62
23.0	457.59	961.0	18680.1	18748.8	34.37	470.76
24.0	411.85	869.4	19478.3	19549.5	35.63	470.87
25.0	366.09	777.9	20182.7	20256.2	36.74	470.98
26.0	320.33	686.4	20793.8	20869.2	37.70	471.06
27.0	274.56	594.9	21311.6	21388.7	38.51	471.14
28.0	228.80	503.4	21736.6	21815.0	39.18	471.20
29.0	183.04	411.8	22069.0	22148.5	39.72	471.25
30.0	137.28	320.3	22307.0	22389.4	41.17	471.28
31.0	91.52	228.8	22451.7	22535.8	42.05	471.30
32.0	45.76	137.3	22504.3	22589.0	42.37	471.31
33.0	0.00	45.8	22465.8	22550.0	42.13	471.31

POND-2 Version: 5.17 S/N:  
EXECUTED: 02-06-1997 13:09:06

\*\*\*\*\* SUMMARY OF ROUTING COMPUTATIONS \*\*\*\*\*

Pond File: 8169 .PND  
Inflow Hydrograph: 8169-25 .HYD  
Outflow Hydrograph: OUT .HYD

Starting Pond W.S. Elevation = 467.75 ft

\*\*\*\*\* Summary of Peak Outflow and Peak Elevation \*\*\*\*\*

Peak Inflow = 594.90 cfs  
Peak Outflow = 42.37 cfs  
Peak Elevation = 471.31 ft

\*\*\*\*\* Summary of Approximate Peak Storage \*\*\*\*\*


Initial Storage = 0.00 ac-ft  
Peak Storage From Storm = 15.53 ac-ft  
-----  
Total Storage in Pond = 15.53 ac-ft

POND-2 Version: 5.17 S/N:

Pond File: 8169 .PND  
 Inflow Hydrograph: 8169-25 .HYD  
 Outflow Hydrograph: OUT .HYD

EXECUTED: 02-06-1997  
 13:09:06

Peak Inflow = 594.90 cfs  
 Peak Outflow = 42.37 cfs  
 Peak Elevation = 471.31 ft



x File: 8169-25 .HYD Qmax = 42.4 cfs  
 \* File: OUT .HYD Qmax = 594.9 cfs

POND-2 Version: 5.17  
S/N:

MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06. 1997

CALCULATED 02-06-1997 13:06:13  
DISK FILE: 8169 .VOL

Planimeter scale: 1 inch = 50 ft.

Elevation (ft)	Planimeter (sq.in.)	Area (acres)	$A1+A2+sr(A1*A2)$ (acres)	* Volume (acre-ft)	Volume Sum (acre-ft)
467.75	69.76	4.00	0.00	0.00	0.00
470.00	76.82	4.41	12.61	9.46	9.46
472.00	88.33	5.07	14.21	9.47	18.93
474.00	101.97	5.85	16.37	10.91	29.84
476.00	117.36	6.74	18.87	12.58	42.42

\* Incremental volume computed by the Conic Method for Reservoir Volumes.

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06. 1997  
\*\*\*\*\*

\*\*\*\*\* COMPOSITE OUTFLOW SUMMARY \*\*\*\*\*

<u>Elevation (ft)</u>	<u>Q (cfs)</u>	<u>Contributing Structures</u>
467.75	0.0	1 +3
468.25	2.3	1 +3
468.75	6.6	1 +3
469.25	12.1	1 +3
469.75	18.7	1 +3
470.25	26.1	1 +3
470.75	34.3	1 +3
471.25	39.7	2 +4
471.75	61.2	2 +4 +5
472.25	137.4	2 +4 +5
472.75	244.1	2 +4 +5
473.25	374.1	2 +4 +5
473.75	523.5	2 +4 +5
474.25	690.0	2 +4 +5
474.75	872.0	2 +4 +5
475.25	1068.3	2 +4 +5
475.75	1277.9	2 +4 +5
476.00	0.0	



Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO.. INC.  
FEBRUARY 06. 1997  
\*\*\*\*\*

Outlet Structure File: 8169 .STR  
Planimeter Input File: 8169 .VOL  
Rating Table Output File: 8169 .PND

Min. Elev.(ft) = 467.75 Max. Elev.(ft) = 476 Incr.(ft) = .5

Additional elevations (ft) to be included in table:  
\*\*\*\*\*

\*\*\*\*\*  
SYSTEM CONNECTIVITY  
\*\*\*\*\*

Structure	No.	Q Table	Q Table
WEIR-VR	1		-> 1
ORIFICE	2	? 1	-> A
WEIR-VR	3		-> 3
ORIFICE	4	? 3	-> B
WEIR-VR	5		-> 5

Outflow rating table summary was stored in file:  
8169 .PND

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17

S/N:

Date Executed:

Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

>>>>> Structure No. 1 <<<<<<  
(Input Data)

WEIR-VR

Weir - Vertical Rectangular

E1 elev.(ft)?	467.75
E2 elev.(ft)?	476.00
Weir coefficient?	3
Weir elev.(ft)?	467.75
Length (ft)?	1.10
Contracted/Suppressed (C/S)?	S

Outlet Structure File: 8169

.STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO.. INC.  
FEBRUARY 06. 1997  
\*\*\*\*\*

>>>>> Structure No. 2 <<<<<<  
(Input Data)

ORIFICE  
Orifice - Based on Area and Datum Elevation

E1 elev.(ft)?	469.00
E2 elev.(ft)?	476.00
Orifice coeff.?	.6
Invert elev.(ft)?	467.75
Datum elev.(ft) ?	469.00
Orifice area (sq ft)?	2.75

Outlet Structures File: 8169 .STR

POND-2 Version: 5.17

S/N:

Date Executed:

Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06. 1997  
\*\*\*\*\*

>>>>> Structure No. 3 <<<<<<  
(Input Data)

WEIR-VR

Weir - Vertical Rectangular

E1 elev.(ft)?	467.75
E2 elev.(ft)?	476.0
Weir coefficient?	3
Weir elev.(ft)?	467.75
Length (ft)?	1.10
Contracted/Suppressed (C/S)?	S

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO.. INC.  
FEBRUARY 06. 1997  
\*\*\*\*\*

>>>>> Structure No. 4 <<<<<<  
(Input Data)

ORIFICE  
Orifice - Based on Area and Datum Elevation

E1 elev.(ft)?	469.00
E2 elev.(ft)?	476.0
Orifice coeff.?	.6
Invert elev.(ft)?	467.75
Datum elev.(ft) ?	469.00
Orifice area (sq ft)?	2.75

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17

S/N:

Date Executed:

Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO.. INC.  
FEBRUARY 06. 1997  
\*\*\*\*\*

>>>>> Structure No. 5 <<<<<<  
(Input Data)

WEIR-VR

Weir - Vertical Rectangular

E1 elev.(ft)?	471.50
E2 elev.(ft)?	476.00
Weir coefficient?	3
Weir elev.(ft)?	471.50
Length (ft)?	46.00
Contracted/Suppressed (C/S)?	S

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO.. INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

Outflow Rating Table for Structure #1  
WEIR-VR Weir - Vertical Rectangular

\*\*\*\*\* INLET CONTROL ASSUMED \*\*\*\*\*

Elevation (ft)	Q (cfs)	Computation Messages
467.75	0.0	H =0.0
468.25	1.2	H =.5
468.75	3.3	H =1.0
469.25	6.1	H =1.5
469.75	9.3	H =2.0
470.25	13.0	H =2.5
470.75	17.1	H =3.0
471.25	21.6	H =3.5
471.75	26.4	H =4.0
472.25	31.5	H =4.5
472.75	36.9	H =5.0
473.25	42.6	H =5.5
473.75	48.5	H =6.0
474.25	54.7	H =6.5
474.75	61.1	H =7.0
475.25	67.8	H =7.5
475.75	74.7	H =8.0
476.00	0.0	E = or > E2=476.00

C = 3 L (ft) = 1.1

H (ft) = Table elev. - Invert elev. ( 467.75 ft )

Q (cfs) = C \* L \* (H\*\*1.5) -- Suppressed Weir

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

Outflow Rating Table for Structure #2  
ORIFICE Orifice - Based on Area and Datum Elevation

<u>Elevation (ft)</u>	<u>Q (cfs)</u>	<u>Computation Messages</u>
467.75	0.0	E < E1=469.00
468.25	0.0	E < E1=469.00
468.75	0.0	E < E1=469.00
469.25	6.6	H =.25
469.75	11.5	H =.750
470.25	14.8	H =1.25
470.75	17.5	H =1.75
471.25	19.9	H =2.25
471.75	22.0	H =2.75
472.25	23.9	H =3.25
472.75	25.6	H =3.75
473.25	27.3	H =4.25
473.75	28.9	H =4.75
474.25	30.3	H =5.25
474.75	31.8	H =5.75
475.25	33.1	H =6.25
475.75	34.4	H =6.75
476.00	0.0	E = or > E2=476.00

C = .6      A = 2.75 sq.ft.  
H (ft) = Table elev. - Datum elev. ( 469 ft )  
Q (cfs) = C \* A \* sqrt(2g \* H)



Outlet Structure File: 8169

.STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO.. INC.  
FEBRUARY 06. 1997  
\*\*\*\*\*

Outflow Rating Table for Structure #3  
WEIR-VR Weir - Vertical Rectangular

\*\*\*\*\* INLET CONTROL ASSUMED \*\*\*\*\*

Elevation (ft)	Q (cfs)	Computation Messages
467.75	0.0	H =0.0
468.25	1.2	H =.5
468.75	3.3	H =1.0
469.25	6.1	H =1.5
469.75	9.3	H =2.0
470.25	13.0	H =2.5
470.75	17.1	H =3.0
471.25	21.6	H =3.5
471.75	26.4	H =4.0
472.25	31.5	H =4.5
472.75	36.9	H =5.0
473.25	42.6	H =5.5
473.75	48.5	H =6.0
474.25	54.7	H =6.5
474.75	61.1	H =7.0
475.25	67.8	H =7.5
475.75	74.7	H =8.0
476.00	0.0	E = or > E2=476.0

C = 3 L (ft) = 1.1

H (ft) = Table elev. - Invert elev. ( 467.75 ft )

Q (cfs) = C \* L \* (H\*\*1.5) -- Suppressed Weir

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17

S/N:

Date Executed:

Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

Outflow Rating Table for Structure #4  
ORIFICE Orifice - Based on Area and Datum Elevation

Elevation (ft)	Q (cfs)	Computation Messages
467.75	0.0	E < E1=469.00
468.25	0.0	E < E1=469.00
468.75	0.0	E < E1=469.00
469.25	6.6	H =.25
469.75	11.5	H =.750
470.25	14.8	H =1.25
470.75	17.5	H =1.75
471.25	19.9	H =2.25
471.75	22.0	H =2.75
472.25	23.9	H =3.25
472.75	25.6	H =3.75
473.25	27.3	H =4.25
473.75	28.9	H =4.75
474.25	30.3	H =5.25
474.75	31.8	H =5.75
475.25	33.1	H =6.25
475.75	34.4	H =6.75
476.00	0.0	E = or > E2=476.0

C = .6      A = 2.75 sq.ft.

H (ft) = Table elev. - Datum elev. ( 469 ft )

Q (cfs) = C \* A \* sqrt(2g \* H)

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06. 1997  
\*\*\*\*\*

Outflow Rating Table for Structure #5  
WEIR-VR Weir - Vertical Rectangular

\*\*\*\*\* INLET CONTROL ASSUMED \*\*\*\*\*

Elevation (ft)	Q (cfs)	Computation Messages
467.75	0.0	E < Inv.El. = 471.5
468.25	0.0	E < Inv.El. = 471.5
468.75	0.0	E < Inv.El. = 471.5
469.25	0.0	E < Inv.El. = 471.5
469.75	0.0	E < Inv.El. = 471.5
470.25	0.0	E < Inv.El. = 471.5
470.75	0.0	E < Inv.El. = 471.5
471.25	0.0	E < Inv.El. = 471.5
471.75	17.3	H = .25
472.25	89.6	H = .750
472.75	192.9	H = 1.25
473.25	319.5	H = 1.75
473.75	465.8	H = 2.25
474.25	629.3	H = 2.75
474.75	808.5	H = 3.25
475.25	1002.1	H = 3.75
475.75	1209.1	H = 4.25
476.00	0.0	E = or > E2=476.00

C = 3    L (ft) = 46  
H (ft) = Table elev. - Invert elev. ( 471.5 ft )  
Q (cfs) = C \* L \* (H\*\*1.5) -- Suppressed Weir

Outlet Structures File: 8169 .STR

POND-2 Version: 5.17

S/N:

Date Executed:

Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

Outflow Rating Table A  
Table A = 1 ? 2

<u>Elevation (ft)</u>	<u>Q (cfs)</u>	<u>Contributing Structures</u>
467.75	0.0	1
468.25	1.2	1
468.75	3.3	1
469.25	6.1	1
469.75	9.3	1
470.25	13.0	1
470.75	17.1	1
471.25	19.9	2
471.75	22.0	2
472.25	23.9	2
472.75	25.6	2
473.25	27.3	2
473.75	28.9	2
474.25	30.3	2
474.75	31.8	2
475.25	33.1	2
475.75	34.4	2
476.00	0.0	-

Outlet Structure File: 8169 .STR


POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

Outflow Rating Table B  
Table B = 3 ? 4

<u>Elevation (ft)</u>	<u>Q (cfs)</u>	<u>Contributing Structures</u>
467.75	0.0	3
468.25	1.2	3
468.75	3.3	3
469.25	6.1	3
469.75	9.3	3
470.25	13.0	3
470.75	17.1	3
471.25	19.9	4
471.75	22.0	4
472.25	23.9	4
472.75	25.6	4
473.25	27.3	4
473.75	28.9	4
474.25	30.3	4
474.75	31.8	4
475.25	33.1	4
475.75	34.4	4
476.00	0.0	-



**PICKETT RAY & SILVER**

PROJECT NAME LONE STAR PHASE II

PROJECT #/JOB ORDER # 86-155F

DATE 9-18-89

DESIGNER DWB. REV. BY JES 9/22/89

PAGE 1 OF 4

333 Mid Rivers Mall Dr  
St. Peters, MO 63376

Civil Engineers  
Planners  
Land Surveyors

441-1211  
278-1211

DETENTION BASIN CALCS:

AREA BEING DEVELOPED:

105.76 ACRES COMMERCIAL @ 4.75 = 502.36 cfs

83.26 ACRES RESIDENTIAL @ 3.26 = 271.43 cfs

TOTAL = ~~189.02 ACRES~~

773.79 cfs  
(DEVELOPED 25 YEAR STORM)

UNDEVELOPED "Q" = 189.02 AC. @ 2.31 cfs = 436.64 cfs

DIFFERENTIAL:

773.79 cfs DEVELOPED (25 YEAR STORM)  
- 436.64 cfs UNDEVELOPED (25 YEAR STORM)  
337.15 cfs TO BE STORED

DETENTION:

337.15 cfs x 30 MIN. x 60 SEC/MIN = 606,870 CU. FT. STORAGE ✓  
(25 YEAR)

STORAGE OF LAKE:

ELEV	AREA SQ. FT.	AVG. SQ. FT.	CU. FT.	CUMMULATIVE CU. FT.
467.75	0	0	0	0
469.00	186,500	93,894	117,368	117,368
470.00	193,788	190,144	190,144	307,512 (STORAGE)
471.00	203,314	198,551	198,551	506,063 ELEV. 471.50
472.00	212,840	208,077	208,077	714,140 608,911 CU. FT. VOLUME Q25 ✓
474.00	231,761	222,301	444,602	1,158,742
476.00	257,864	244,813	489,626	1,648,368
STORAGE: 25 YEAR/30 MIN STORM				ELEV. 471.50 = 608,911 CU. FT.

**PICKETT RAY & SILVER**

333 Mid Rivers Mall Dr  
St. Peters, MO 63376

Civil Engineers  
Planners  
Land Surveyors

441-1211  
278-1211

PROJECT NAME LONE STAR PHASE II  
PROJECT #/JOB ORDER # 86-155F  
DATE 9-18-89  
DESIGNER D.W.B. REV. BY J.E.S. 9/22/89  
PAGE 2 OF 4

<u>DRAINAGE AREAS TO BASIN : (15 YEAR STORM)</u>	
DA#1	28.7 Ac. @ 3.85 cfs = 110.50 cfs
DA#3	55.3 Ac. @ 2.64 cfs = 145.99 cfs
DA#4	52.7 Ac. @ 2.64 cfs = 139.13 cfs
TOTAL "Q" TO BASIN = 395.62 cfs (15 YEAR STORM)	
<u>DEVELOPED AREAS BY PASSING BASIN : (15 YEAR STORM)</u>	
DA#2	65.5 Ac. @ 3.85 = 252.18 cfs
DA#5	22.0 Ac. @ 2.64 = 58.08 cfs
TOTAL "Q" BY-PASSING BASIN = 310.26 cfs	
<u>ALLOWABLE OUTFLOW : = ±200 cfs</u>	
	353.47 cfs UNDEVELOPED "Q'S"
	310.26 cfs BY-PASS
	43.21 cfs (MAXIMUM ALLOWABLE OUTFALL FROM SLOTS)
<u>LOW FLOW CALCULATIONS :</u>	
ORIFICE FORMULA	$Q = C_d \sqrt{2gh}$
	$Q = 0.61 \times 2.76 \times \sqrt{(2 \times 32.2)(2.50)}$
	$Q = 1.68 \times 12.69$
	$Q = 21.32 \text{ cfs (PER SLOT RELEASE)}$
2 SLOTS @ 21.32 cfs = 42.64 cfs @ ELEV. 475.50	
<u>OVERFLOW STRUCTURE : (15 YEAR STORM)</u>	
WEIR FORMULA	$Q = CLH^{3/2}$
	$395.62 \text{ cfs} = 3.0 \times 46 \times H^{3/2}$
	$2.87 = H^{3/2}$
	$2.02 = H$
471.50 + 2.02 = 473.52 - ELEV. TO PASS 15 YEAR STORM	



**PICKETT RAY & SILVER**

PROJECT NAME LONE STAR PHASE II  
 PROJECT #/JOB ORDER # 86-155F  
 DATE 9-18-89  
 DESIGNER DWB REV. BYTES 9/22/89  
 PAGE 3 OF 4

DRAINAGE 25 YEAR STORM TO BASIN:		OVERFLOW STRUCTURE:	
DA#1 28.7 AC @ 4.75 =	136.93 CFS	DA#1 28.7 AC @ 6.08 CFS =	174.50 CFS
DA#3 55.3 AC @ 3.26 =	180.28 CFS	DA#3 55.3 AC @ 4.17 CFS =	230.60 CFS
DA#4 52.7 AC @ 3.26 =	171.80 CFS	DA#4 52.7 AC @ 4.17 CFS =	219.76 CFS
TOTAL "Q <sup>25</sup> " TO BASIN =		TOTAL "Q <sup>100</sup> " TO BASIN =	
488.41 CFS (25 YEAR STORM)		624.86 CFS (100 YEAR STORM)	
DRAINAGE 100 YEAR STORM TO BASIN:		OVERFLOW STRUCTURE:	
$Q^{25} = CL H^{3/2}$ $488.41 CFS = 30 \times 46 \times H^{3/2}$ $3.54 = H^{3/2}$ $2.32 = H$		$Q = CL H^{3/2}$ $624.86 CFS = 30 \times 46 \times H^{3/2}$ $4.52 = H^{3/2}$ $2.73 = H$	
$471.50 + 2.32 = 473.82 = \text{ELEV. TO PASS 25 YEAR STORM}$		$471.50 + 2.73 = 474.24 = \text{ELEV. TO PASS 100 YEAR STORM}$	
<p>NOTE: SET TOP OF DAM @ 474.24 + 1.76 = 476.00 MIN.</p>		<p>FREEBOARD</p>	


# PICKETT RAY & SILVER

Civil Engineers  
Planners  
Land Surveyors

333 Mid Rivers Mall Dr  
St. Peters, MO 63376

441-1211  
278-1211

PROJECT NAME LOW STAR PHASE II  
PROJECT #/JOB ORDER # 86-125F  
DATE REV. 9-18-89  
DESIGNER DWB REV. BY M.G.G. REV. J.E.S.  
PAGE 4 OF 4





ENGINEERING

PLANNING

SURVEYING

**STORMWATER DETENTION ANALYSIS**  
**MANDERLEY ESTATES - O'FALLON**  
**PREPARED BY: BAX ENGINEERING CO., INC.**  
**BAX PROJECT NO. 96-8169**  
**NOVEMBER 15, 1996**  
**REVISED DECEMBER 11, 1996**  
**REVISED FEBRUARY 6, 1997**

INTRODUCTION:

The tract of land is presently an undeveloped site located in the City of O'Fallon, Missouri. It is proposed that the tract, consisting of 52.50 acres, be developed into a single family residential subdivision. An existing lake and stormwater detention basin near the Northeast corner of the site will provide detention for the development, along with detention for Lone Star Industrial Park which consists of 105.76 Acres, as required by the City of O'Fallon. The storage volume and outflow rates shall be proportioned to insure that the peak rate of runoff leaving the site under post-developed conditions is less than or equal to the peak rate of runoff leaving the site under pre-developed conditions for the required design storms. The basin shall be analyzed for both the 15 year frequency - 20 minute and the 25 year frequency - 20 minute duration design storms. The 100 year frequency - 20 minute design storm will be checked for safe passage.

GENERAL SITE DATA AND RUNOFF CALCULATIONS:

Site area: 52.50 Acres

The pre-developed P.I. factors to be used for analysis are:

ONSITE: 15 year - 20 minute storm (assumed 5% impervious): 1.87 c.f.s./Ac  
LONE STAR IND. PARK: 15 year - 20 minute storm (assumed 5% impervious): 1.87 c.f.s./Ac  
OFFSITE: 15 year - 20 minute storm (assumed 40% impervious): 2.64 c.f.s./Ac  
OFFSITE: 15 year - 20 minutes storm (assumed 100% impervious): 3.85 c.f.s./Ac

The post-developed P.I. factors to be used for analysis are:

ONSITE: 15 year - 20 minute storm (developed single family): 2.09 c.f.s./Ac  
LONE STAR IND. PARK: 15 year - 20 minute storm (developed heavy industrial): 3.85 c.f.s./Ac  
OFFSITE: 15 year - 20 minute storm (assumed 40% impervious): 2.64 c.f.s./Ac  
OFFSITE: 15 year - 20 minute storm (assumed 100% impervious): 3.85 c.f.s./Ac

BAX ENGINEERING CO., INC.  
1052 South Cloverleaf Drive  
St. Peters, MO 63376-6445  
314-928-5552 FAX 928-1718



ENGINEERING

PLANNING

SURVEYING

The pre-developed P.I. factors to be used for analysis are:

ONSITE: 25 year - 20 minute storm (assumed 5% impervious): 2.31 c.f.s./Ac  
LONE STAR IND. PARK: 25 year - 20 minute storm (assumed 5% impervious): 2.31 c.f.s./Ac  
OFFSITE: 25 year - 20 minute storm (assumed 40% impervious): 3.26 c.f.s./Ac.  
OFFSITE: 25 year - 20 minutes storm (assumed 100% impervious): 4.75 c.f.s./Ac.

The post-developed P.I. factors to be used for analysis are:

ONSITE: 25 year - 20 minute storm (developed single family): 2.58 c.f.s./Ac  
LONE STAR IND. PARK: 25 year - 20 minute storm (developed heavy industrial): 4.75 c.f.s./Ac  
OFFSITE: 25 year - 20 minute storm (assumed 40% impervious): 3.26 c.f.s./Ac.  
OFFSITE: 25 year - 20 minute storm (assumed 100% impervious): 4.75 c.f.s./Ac.

#### TIME OF CONCENTRATION:

Of the inflows to the basin, the most remote point of origination lies offsite to the Southwest. It will flow approximately 1,400 feet over pavement, then an additional 1,300 feet overland, then an additional 200 feet via storm sewer and then another 335 feet overland to the detention basin. Time of concentration is estimated as follows:

T(pavement): L = 1,400 feet  
Elevation difference = 580 - 520 = 60 feet  
T(pavement) = 2.80 minutes: See Figure 1

T(overland): L = 1,300 feet  
Elevation difference = 520 - 480 = 40 feet  
T(overland) = 7.5 minutes: See Figure 1

T(stormpipe): L = 200 feet  
Estimated velocity 7 feet/second  
T(stormpipe) =  $\frac{200 \text{ feet}}{7 \text{ feet/sec}}$   
= 28.57 seconds = 0.48 minutes

T(overland): L = 335 feet  
Elevation difference = 476 - 468.5 = 7.5 feet  
T(overland) = 2.85 minutes: See Figure 1

Total Time: T(overland) + T(storm pipe) + T(overland) + T(pavement)  
= 2.85 min. + 0.48 min. + 7.50 min. + 2.80 min. = 13.63 min. => use 13.0 minutes





ENGINEERING

PLANNING

SURVEYING

REQUIRED ATTENUATION

Tract Area x [PI(post) - PI(pre)]

15 year - 20 minutes storm

On-site = 52.50 x (2.09 - 1.87) = 11.55 c.f.s.

Lone Star Industrial Park = 105.76 x (3.85 - 1.87) = 209.40 c.f.s.

Total 220.95 c.f.s.

BASIN PEAK INFLOW

Inflows to the basin have been estimated from the drainage area map of the project. (See Construction Plans)

PRE-DEVELOPED RUNOFF (15 year - 20 minute storm)

Flow going to the basin:

On-site areas (assumed 5% impervious)

15 year - 20 minute storm  $Q_{pre}$  = 30.19 acres @ 1.87 = 56.46 c.f.s.

Lone Star Industrial Park areas (assumed 5% impervious)

15 year - 20 minute storm  $Q_{pre}$  = 51.81 acres @ 1.87 = 96.88 c.f.s.

Off-site areas (assumed 100% impervious)

15 year - 20 minute storm  $Q_{pre}$  = 49.19 acres @ 3.85 = 189.38 c.f.s.

Off-site areas (assumed 40% impervious)

15 year - 20 minute storm  $Q_{pre}$  = 11.43 acres @ 2.64 = 30.18 c.f.s.

Total 372.90 c.f.s.

100 year - 20 minute storm = 15 year - 20 minute storm x 1.58  
= 372.90 c.f.s. x 1.58 = 589.18 c.f.s.

Flow Bypassing the Basin:

On-site areas (assumed 5% impervious)

15 year - 20 minute storm  $Q_{pre}$  = 22.28 acres @ 1.87 = 41.66 c.f.s.



ENGINEERING

PLANNING

SURVEYING

Lone Star Industrial Park areas (assumed 5% impervious)

15 year - 20 minute storm  $Q_{pre} = 53.95 \text{ acres @ } 1.87 = 100.89 \text{ c.f.s.}$

Off-site areas (assumed 40% impervious)

15 year - 20 minute storm  $Q_{pre} = 27.0 \text{ acres @ } 2.64 = 71.28 \text{ c.f.s.}$

Total 213.83 c.f.s.

100 year - 20 minute storm = 15 year - 20 minute storm x 1.58  
= 213.83 c.f.s. x 1.58 = 337.85 c.f.s.

POST-DEVELOPED RUNOFF (15 year - 20 minute storm)

Flow going to the Basin:

On-site areas (assumed 15% impervious)

15 year - 20 minute storm  $Q_{post} = 30.19 \text{ acres @ } 2.09 = 63.10 \text{ c.f.s.}$

Lone Star Industrial Park (assumed 100% impervious)

15 year - 20 minute storm  $Q_{post} = 51.81 \text{ acres @ } 3.85 = 199.47 \text{ c.f.s.}$

Off-site areas (assumed 100% impervious)

15 year - 20 minute storm  $Q_{post} = 49.19 \text{ acres @ } 3.85 = 189.38 \text{ c.f.s.}$

Off-site areas (assumed 40% impervious)

15 year - 20 minute storm  $Q_{post} = 11.43 \text{ acres @ } 2.64 = 30.18 \text{ c.f.s.}$

Total 482.13 c.f.s.

100 year - 20 minute storm = 15 year - 20 minute storm x 1.58

= 482.13 c.f.s. x 1.58 = 761.77 c.f.s.

Flow Bypassing the Basin:

On-site areas (assumed 15% impervious)

15 year - 20 minute storm  $Q_{post} = 22.28 \text{ acres @ } 2.09 = 46.57 \text{ c.f.s.}$

Lone Star Industrial Park areas (assumed 100% impervious)

15 year - 20 minute storm  $Q_{post} = 53.95 \text{ acres @ } 3.85 = 207.71 \text{ c.f.s.}$



ENGINEERING

PLANNING

Off-site areas (assumed 40% impervious) *SURVEYING*  
15 year - 20 minute storm  $Q_{\text{post}} = 27.0 \text{ acres @ } 2.64 = 71.28 \text{ c.f.s.}$

Total 325.56 c.f.s.

100 year - 20 minute storm = 15 year - 20 minute storm x 1.58  
= 325.56 c.f.s. x 1.58 = 514.38 c.f.s.

### PERMITTED RELEASE RATE

The permitted release rate of the detention basin is found by subtracting the total required attenuation from the post-developed peak inflow to the basin for the design storm.

15 year - 20 minute storm  
Permitted release rate = 482.13 c.f.s. - 220.95 c.f.s.  
= 261.18 c.f.s.

### ROUTING CALCULATIONS AND RESULTS

A computer program "Pondpack" was utilized in routing the design storms through the basin. As found in the routing calculations, the results of each analysis are as follows:

15 year - 20 minute storm:  
Peak release rate = 33.43 (< 261.18 c.f.s.)  
Peak elevation = 470.70

### REQUIRED ATTENUATION

Tract Area x [PI(post) - PI(pre)]

25 year - 20 minutes storm

On-site = 52.50 x (2.58 - 2.31) = 14.18 c.f.s.

Lone Star Industrial Park = 105.76 x (4.75 - 2.31) = 258.05 c.f.s.

Total 272.23 c.f.s.

### BASIN PEAK INFLOW

Inflows to the basin have been estimated from the drainage area map of the project. (See Construction Plans)



ENGINEERING

PLANNING

SURVEYING

### PRE-DEVELOPED RUNOFF (25 year - 20 minute storm)

Flow going to the basin:

On-site areas (assumed 5% impervious)

$$25 \text{ year - 20 minute storm } Q_{pre} = 30.19 \text{ acres @ } 2.31 = 69.74 \text{ c.f.s.}$$

Lone Star Industrial Park areas (assumed 5% impervious)

$$25 \text{ year - 20 minute storm } Q_{pre} = 51.81 \text{ acres @ } 2.31 = 119.68 \text{ c.f.s.}$$

Off-site areas (assumed 100% impervious)

$$25 \text{ year - 20 minute storm } Q_{pre} = 49.19 \text{ acres @ } 4.75 = 233.65 \text{ c.f.s.}$$

Off-site areas (assumed 40% impervious)

$$25 \text{ year - 20 minute storm } Q_{pre} = 11.43 \text{ acres @ } 3.26 = 37.26 \text{ c.f.s.}$$

Total 460.33 c.f.s.

$$\begin{aligned} 100 \text{ year - 20 minute storm} &= 25 \text{ year - 20 minute storm} \times 1.28 \\ &= 460.33 \text{ c.f.s.} \times 1.28 = 589.22 \text{ c.f.s.} \end{aligned}$$

Flow Bypassing the Basin:

On-site areas (assumed 5% impervious)

$$25 \text{ year - 20 minute storm } Q_{pre} = 22.28 \text{ acres @ } 2.31 = 51.47 \text{ c.f.s.}$$

Lone Star Industrial Park areas (assumed 5% impervious)

$$25 \text{ year - 20 minute storm } Q_{pre} = 53.95 \text{ acres @ } 2.31 = 124.62 \text{ c.f.s.}$$

Off-site areas (assumed 40% impervious)

$$25 \text{ year - 20 minute storm } Q_{pre} = 27.0 \text{ acres @ } 3.26 = 88.02 \text{ c.f.s.}$$

Total 264.11 c.f.s.

$$\begin{aligned} 100 \text{ year - 20 minute storm} &= 25 \text{ year - 20 minute storm} \times 1.28 \\ &= 264.11 \text{ c.f.s.} \times 1.28 = 338.06 \text{ c.f.s.} \end{aligned}$$

### POST-DEVELOPED RUNOFF (25 year - 20 minute storm)

Flow going to the Basin:

On-site areas (assumed 15% impervious)

$$25 \text{ year - 20 minute storm } Q_{post} = 30.19 \text{ acres @ } 2.58 = 77.89 \text{ c.f.s.}$$





ENGINEERING

PLANNING

SURVEYING

Lone Star Industrial Park (assumed 100% impervious)

$$25 \text{ year - 20 minute storm } Q_{\text{post}} = 51.81 \text{ acres @ } 4.75 = 246.10 \text{ c.f.s.}$$

Off-site areas (assumed 100% impervious)

$$25 \text{ year - 20 minute storm } Q_{\text{post}} = 49.19 \text{ acres @ } 4.75 = 233.65 \text{ c.f.s.}$$

Off-site areas (assumed 40% impervious)

$$25 \text{ year - 20 minute storm } Q_{\text{post}} = 11.43 \text{ acres @ } 3.26 = 37.26 \text{ c.f.s.}$$

$$\text{Total} \qquad \qquad \qquad 594.90 \text{ c.f.s.}$$

$$100 \text{ year - 20 minute storm} = 25 \text{ year - 20 minute storm} \times 1.28$$

$$= 594.90 \text{ c.f.s.} \times 1.28 = 761.47 \text{ c.f.s.}$$

Flow Bypassing the Basin:

On-site areas (assumed 15% impervious)

$$25 \text{ year - 20 minute storm } Q_{\text{post}} = 22.28 \text{ acres @ } 2.58 = 57.48 \text{ c.f.s.}$$

Lone Star Industrial Park areas (assumed 100% impervious)

$$25 \text{ year - 20 minute storm } Q_{\text{post}} = 53.95 \text{ acres @ } 4.75 = 256.26 \text{ c.f.s.}$$

Off-site areas (assumed 40% impervious)

$$25 \text{ year - 20 minute storm } Q_{\text{post}} = 27.0 \text{ acres @ } 3.26 = 88.02 \text{ c.f.s.}$$

$$\text{Total} \qquad \qquad \qquad 401.76 \text{ c.f.s.}$$

$$100 \text{ year - 20 minute storm} = 25 \text{ year - 20 minute storm} \times 1.28$$

$$= 401.76 \text{ c.f.s.} \times 1.28 = 514.25 \text{ c.f.s.}$$

### PERMITTED RELEASE RATE

The permitted release rate of the detention basin is found by subtracting the total required attenuation from the post-developed peak inflow to the basin for the design storm.

25 year - 20 minute storm

$$\text{Permitted release rate} = 594.90 \text{ c.f.s.} - 272.23 \text{ c.f.s.}$$

$$= 322.67 \text{ c.f.s.}$$



ENGINEERING

PLANNING

SURVEYING

## ROUTING CALCULATIONS AND RESULTS

A computer program "Pondpack" was utilized in routing the design storms through the basin. As found in the routing calculations, the results of each analysis are as follows:

25 year - 20 minute storm:

Peak release rate = 42.37 (< 322.67 c.f.s.)

Peak elevation = 471.31

\*100 year - 20 minute storm: (worst case)

Weir Elevation = 471.50

$Q = CLH^{1.5}$

$Q = 761.77$  c.f.s.

$C = 3.0$

$L = 46.0$  feet

$H = 3.20$  feet

Elev. = 474.70

Freeboard = 476.00 - 474.70 = 1.30 feet

Check

$Q = 3.0 (46.0)(3.20)^{1.5}$

$Q = 789.96$  c.f.s.

789.96 c.f.s. > 761.77 c.f.s.

## CHECKING DISCHARGE PIPES

100 year - 20 minute storm: (see Page 10)

$Q = 761.77$  c.f.s.

Existing Discharge Pipes: 2-72" CMP

Flowline of Existing Pipes: 462.50

Check under inlet control

$HW/D = 1.7 \Rightarrow 1.7 \times 72" = 10.2$  feet

Elevation = 462.50 + 10.2 = 472.70 Controls

## DETENTION BASIN CHARACTERISTICS SUMMARY:

15 year - 20 minute storm highwater = 470.70

25 year - 20 minute storm highwater = 471.31

100 year - 20 minute storm highwater = 474.70



*ENGINEERING*

*PLANNING*

*SURVEYING*

Overflow Structure:

Existing concrete structure with grate inlet top

Flowline of the two existing 72" CMP = 462.50

Flowline of low flow slot - (13.2" w x 30" h) = 467.75

Flowline of emergency overflow = 471.50

\*Note: The 100 year - 20 minute storm was checked for safe passage through the basin in a worst case situation with the low flow opening blocked.



Project: MANTERLEY PLACE

Date: 2-6-97 Project No: 96-8169

Designed: MRK Checked: \_\_\_\_\_


CHART 2

$D = 2$  Existing 72" CIP  
 $TQ = 761.77$  c.f.s.  
 $\frac{TQ}{2} = 380.89$  c.f.s.

$D = 72"$

$R = 462.50$

$H_w + R = 472.50$




HEADWATER DEPTH FOR CONCRETE PIPE CULVERTS WITH INLET CONTROL

HEADWATER SCALES 2 & 3  
 REVISED MAY 1964

BUREAU OF PUBLIC ROADS JAN. 1963

1052 South Cloverleaf Drive  
 St. Peters, MO 63376-6445  
 314-928-5552 FAX 928-1718



$T_c(\text{overland}) = 7.5 \text{ minutes}$   
 $T_c(\text{pavement}) = 7.0 \text{ min.} \times 0.4 = 2.80 \text{ minutes}$   
 $T_c(\text{overland}) = 2.85 \text{ minutes}$

FIGURE 1

TIME OF CONCENTRATION OF SMALL DRAINAGE BASINS



>>>> HYDROGRAPH PRINTOUT <<<<<

02-06-1997 13:05:28

Hydrograph file: 8169-15 .HYD

HYDROGRAPH ORDINATES (cfs)  
 Time increment = 1.00 Minutes

Time :  
 Minutes: Time on left represents time for first Q in each row.

0.00	0.00	37.09	74.17	111.26	148.35	185.44	222.52
7.00	259.61	296.70	333.78	370.87	407.96	445.04	482.13
14.00	482.13	482.13	482.13	482.13	482.13	482.13	482.13
21.00	445.04	407.96	370.87	333.78	296.70	259.61	222.52
28.00	185.44	148.35	111.26	74.17	37.09	0.00	

>>>> HYDROGRAPH PRINTOUT <<<<<

02-06-1997 13:05:48

Hydrograph file: 8169-25 .HYD

HYDROGRAPH ORDINATES (cfs)  
Time increment = 1.00 Minutes  
Time on left represents time for first Q in each row.

Time Minutes							
0.00	0.00	45.76	91.52	137.28	183.04	228.80	274.56
7.00	320.33	366.09	411.85	457.59	503.37	549.13	594.90
14.00	594.90	594.90	594.90	594.90	594.90	594.90	594.90
21.00	549.13	503.37	457.59	411.85	366.09	320.33	274.56
28.00	228.80	183.04	137.28	91.52	45.76	0.00	



POND-2 Version: 5.17  
S/N:

MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06. 1997

CALCULATED 02-06-1997 13:06:13  
DISK FILE: 8169 .VOL

Planimeter scale: 1 inch = 50 ft.

Elevation (ft)	Planimeter (sq.in.)	Area (acres)	$A1+A2+\sqrt{A1*A2}$ (acres)	* Volume (acre-ft)	Volume Sum (acre-ft)
467.75	69.76	4.00	0.00	0.00	0.00
470.00	76.82	4.41	12.61	9.46	9.46
472.00	88.33	5.07	14.21	9.47	18.93
474.00	101.97	5.85	16.37	10.91	29.84
476.00	117.36	6.74	18.87	12.58	42.42

\* Incremental volume computed by the Conic Method for Reservoir Volumes.

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

\*\*\*\*\* COMPOSITE OUTFLOW SUMMARY \*\*\*\*\*

Elevation (ft)	Q (cfs)	Contributing Structures
467.75	0.0	1 +3
468.25	2.3	1 +3
468.75	6.6	1 +3
469.25	12.1	1 +3
469.75	18.7	1 +3
470.25	26.1	1 +3
470.75	34.3	1 +3
471.25	39.7	2 +4
471.75	61.2	2 +4 +5
472.25	137.4	2 +4 +5
472.75	244.1	2 +4 +5
473.25	374.1	2 +4 +5
473.75	523.5	2 +4 +5
474.25	690.0	2 +4 +5
474.75	872.0	2 +4 +5
475.25	1068.3	2 +4 +5
475.75	1277.9	2 +4 +5
476.00	0.0	

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06. 1997  
\*\*\*\*\*

Outlet Structure File: 8169 .STR  
Planimeter Input File: 8169 .VOL  
Rating Table Output File: 8169 .PND

Min. Elev.(ft) = 467.75 Max. Elev.(ft) = 476 Incr.(ft) = .5

Additional elevations (ft) to be included in table:  
\*\*\*\*\*

\*\*\*\*\*  
SYSTEM CONNECTIVITY  
\*\*\*\*\*

Structure	No.	Q Table	Q Table
WEIR-VR	1		-> 1
ORIFICE	2	? 1	-> A
WEIR-VR	3		-> 3
ORIFICE	4	? 3	-> B
WEIR-VR	5		-> 5

Outflow rating table summary was stored in file:  
8169 .PND

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

>>>>> Structure No. 1 <<<<<<  
(Input Data)

WEIR-VR  
Weir - Vertical Rectangular

E1 elev.(ft)?	467.75
E2 elev.(ft)?	476.00
Weir coefficient?	3
Weir elev.(ft)?	467.75
Length (ft)?	1.10
Contracted/Suppressed (C/S)?	S

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

>>>>> Structure No. 2 <<<<<<  
(Input Data)

ORIFICE  
Orifice - Based on Area and Datum Elevation

E1 elev.(ft)?	469.00
E2 elev.(ft)?	476.00
Orifice coeff.?	.6
Invert elev.(ft)?	467.75
Datum elev.(ft) ?	469.00
Orifice area (sq ft)?	2.75

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

>>>>> Structure No. 3 <<<<<<  
(Input Data)

WEIR-VR  
Weir - Vertical Rectangular

E1 elev.(ft)?	467.75
E2 elev.(ft)?	476.0
Weir coefficient?	3
Weir elev.(ft)?	467.75
Length (ft)?	1.10
Contracted/Suppressed (C/S)?	S

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06. 1997  
\*\*\*\*\*

>>>>> Structure No. 4 <<<<<<  
(Input Data)

ORIFICE  
Orifice - Based on Area and Datum Elevation

E1 elev.(ft)?	469.00
E2 elev.(ft)?	476.0
Orifice coeff.?	.6
Invert elev.(ft)?	467.75
Datum elev.(ft) ?	469.00
Orifice area (sq ft)?	2.75

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

>>>>> Structure No. 5 <<<<<<  
(Input Data)

WEIR-VR  
Weir - Vertical Rectangular

E1 elev.(ft)?	471.50
E2 elev.(ft)?	476.00
Weir coefficient?	3
Weir elev.(ft)?	471.50
Length (ft)?	46.00
Contracted/Suppressed (C/S)?	S



Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

Outflow Rating Table for Structure #1  
WEIR-VR Weir - Vertical Rectangular

\*\*\*\*\* INLET CONTROL ASSUMED \*\*\*\*\*

<u>Elevation (ft)</u>	<u>Q (cfs)</u>	<u>Computation Messages</u>
467.75	0.0	H =0.0
468.25	1.2	H =.5
468.75	3.3	H =1.0
469.25	6.1	H =1.5
469.75	9.3	H =2.0
470.25	13.0	H =2.5
470.75	17.1	H =3.0
471.25	21.6	H =3.5
471.75	26.4	H =4.0
472.25	31.5	H =4.5
472.75	36.9	H =5.0
473.25	42.6	H =5.5
473.75	48.5	H =6.0
474.25	54.7	H =6.5
474.75	61.1	H =7.0
475.25	67.8	H =7.5
475.75	74.7	H =8.0
476.00	0.0	E = or > E2=476.00

C = 3      L (ft) = 1.1  
H (ft) = Table elev. - Invert elev. ( 467.75 ft )  
Q (cfs) = C \* L \* (H\*\*1.5) -- Suppressed Weir

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

Outflow Rating Table for Structure #2  
ORIFICE Orifice - Based on Area and Datum Elevation

Elevation (ft)	Q (cfs)	Computation Messages
467.75	0.0	E < E1=469.00
468.25	0.0	E < E1=469.00
468.75	0.0	E < E1=469.00
469.25	6.6	H =.25
469.75	11.5	H =.750
470.25	14.8	H =1.25
470.75	17.5	H =1.75
471.25	19.9	H =2.25
471.75	22.0	H =2.75
472.25	23.9	H =3.25
472.75	25.6	H =3.75
473.25	27.3	H =4.25
473.75	28.9	H =4.75
474.25	30.3	H =5.25
474.75	31.8	H =5.75
475.25	33.1	H =6.25
475.75	34.4	H =6.75
476.00	0.0	E = or > E2=476.00

C = .6      A = 2.75 sq.ft.

H (ft) = Table elev. - Datum elev. ( 469 ft )

Q (cfs) = C \* A \* sqr(2g \* H)

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

Outflow Rating Table for Structure #3  
WEIR-VR Weir - Vertical Rectangular

\*\*\*\*\* INLET CONTROL ASSUMED \*\*\*\*\*

Elevation (ft)	Q (cfs)	Computation Messages
467.75	0.0	H =0.0
468.25	1.2	H =.5
468.75	3.3	H =1.0
469.25	6.1	H =1.5
469.75	9.3	H =2.0
470.25	13.0	H =2.5
470.75	17.1	H =3.0
471.25	21.6	H =3.5
471.75	26.4	H =4.0
472.25	31.5	H =4.5
472.75	36.9	H =5.0
473.25	42.6	H =5.5
473.75	48.5	H =6.0
474.25	54.7	H =6.5
474.75	61.1	H =7.0
475.25	67.8	H =7.5
475.75	74.7	H =8.0
476.00	0.0	E = or > E2=476.0

C = 3 L (ft) = 1.1

H (ft) = Table elev. - Invert elev. ( 467.75 ft )

Q (cfs) = C \* L \* (H\*\*1.5) -- Suppressed Weir

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

Outflow Rating Table for Structure #4  
ORIFICE Orifice - Based on Area and Datum Elevation

Elevation (ft)	Q (cfs)	Computation Messages
467.75	0.0	E < E1=469.00
468.25	0.0	E < E1=469.00
468.75	0.0	E < E1=469.00
469.25	6.6	H =.25
469.75	11.5	H =.750
470.25	14.8	H =1.25
470.75	17.5	H =1.75
471.25	19.9	H =2.25
471.75	22.0	H =2.75
472.25	23.9	H =3.25
472.75	25.6	H =3.75
473.25	27.3	H =4.25
473.75	28.9	H =4.75
474.25	30.3	H =5.25
474.75	31.8	H =5.75
475.25	33.1	H =6.25
475.75	34.4	H =6.75
476.00	0.0	E = or > E2=476.0

C = .6     A = 2.75 sq.ft.

H (ft) = Table elev. - Datum elev. ( 469 ft )

Q (cfs) = C \* A \* sqr(2g \* H)

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO.. INC.  
FEBRUARY 06. 1997  
\*\*\*\*\*

Outflow Rating Table for Structure #5  
WEIR-VR Weir - Vertical Rectangular

\*\*\*\*\* INLET CONTROL ASSUMED \*\*\*\*\*

Elevation (ft)	Q (cfs)	Computation Messages
467.75	0.0	E < Inv.El.= 471.5
468.25	0.0	E < Inv.El.= 471.5
468.75	0.0	E < Inv.El.= 471.5
469.25	0.0	E < Inv.El.= 471.5
469.75	0.0	E < Inv.El.= 471.5
470.25	0.0	E < Inv.El.= 471.5
470.75	0.0	E < Inv.El.= 471.5
471.25	0.0	E < Inv.El.= 471.5
471.75	17.3	H =.25
472.25	89.6	H =.750
472.75	192.9	H =1.25
473.25	319.5	H =1.75
473.75	465.8	H =2.25
474.25	629.3	H =2.75
474.75	808.5	H =3.25
475.25	1002.1	H =3.75
475.75	1209.1	H =4.25
476.00	0.0	E = or > E2=476.00

C = 3 L (ft) = 46

H (ft) = Table elev. - Invert elev. ( 471.5 ft )

Q (cfs) = C \* L \* (H\*\*1.5) -- Suppressed Weir

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

Outflow Rating Table A  
Table A = 1 ? 2

<u>Elevation (ft)</u>	<u>Q (cfs)</u>	<u>Contributing Structures</u>
467.75	0.0	1
468.25	1.2	1
468.75	3.3	1
469.25	6.1	1
469.75	9.3	1
470.25	13.0	1
470.75	17.1	1
471.25	19.9	2
471.75	22.0	2
472.25	23.9	2
472.75	25.6	2
473.25	27.3	2
473.75	28.9	2
474.25	30.3	2
474.75	31.8	2
475.25	33.1	2
475.75	34.4	2
476.00	0.0	-

Outlet Structure File: 8169 .STR

POND-2 Version: 5.17  
Date Executed:

S/N:  
Time Executed:

\*\*\*\*\*  
MANDERLEY ESTATES  
DETENTION ANALYSIS  
PREPARED BY: BAX ENGINEERING CO., INC.  
FEBRUARY 06, 1997  
\*\*\*\*\*

Outflow Rating Table B  
Table B = 3 ? 4

<u>Elevation (ft)</u>	<u>Q (cfs)</u>	<u>Contributing Structures</u>
467.75	0.0	3
468.25	1.2	3
468.75	3.3	3
469.25	6.1	3
469.75	9.3	3
470.25	13.0	3
470.75	17.1	3
471.25	19.9	4
471.75	22.0	4
472.25	23.9	4
472.75	25.6	4
473.25	27.3	4
473.75	28.9	4
474.25	30.3	4
474.75	31.8	4
475.25	33.1	4
475.75	34.4	4
476.00	0.0	-

```

*****
*
*           MANDERLEY ESTATES
*         DETENTION ANALYSIS
*   PREPARED BY: BAX ENGINEERING CO., INC.
*           FEBRUARY 06. 1997
*
*****
  
```

Inflow Hydrograph: 8169-15 .HYD  
 Rating Table file: 8169 .PND

----INITIAL CONDITIONS----  
 Elevation = 467.75 ft  
 Outflow = 0.00 cfs  
 Storage = 0.00 ac-ft

GIVEN POND DATA			INTERMEDIATE ROUTING COMPUTATIONS	
ELEVATION (ft)	OUTFLOW (cfs)	STORAGE (ac-ft)	2S/t (cfs)	2S/t + 0 (cfs)
467.75	0.0	0.000	0.0	0.0
468.25	2.3	2.024	2938.7	2941.0
468.75	6.6	4.092	5941.8	5948.4
469.25	12.1	6.205	9010.2	9022.3
469.75	18.7	8.364	12144.5	12163.2
470.25	26.1	10.573	15351.5	15377.6
470.75	34.3	12.858	18669.1	18703.4
471.25	39.7	15.224	22105.7	22145.4
471.75	61.2	17.674	25663.1	25724.3
472.25	137.4	20.210	29345.2	29482.6
472.75	244.1	22.840	33164.0	33408.1
473.25	374.1	25.567	37123.6	37497.7
473.75	523.5	28.393	41226.5	41750.0
474.25	690.0	31.320	45476.3	46166.3
474.75	872.0	34.354	49881.3	50753.3
475.25	1068.3	37.497	54445.1	55513.4
475.75	1277.9	40.751	59170.7	60448.6

Time increment (t) = 1.0 min.



Pond File: 8169 .PND  
 Inflow Hydrograph: 8169-15 .HYD  
 Outflow Hydrograph: OUT .HYD

INFLOW HYDROGRAPH

ROUTING COMPUTATIONS

TIME (min)	INFLOW (cfs)	I1+I2 (cfs)	2S/t - 0 (cfs)	2S/t + 0 (cfs)	OUTFLOW (cfs)	ELEVATION (ft)
0.0	0.00	-----	0.0	0.0	0.00	467.75
1.0	37.09	37.1	37.0	37.1	0.03	467.76
2.0	74.17	111.3	148.1	148.3	0.12	467.78
3.0	111.26	185.4	333.0	333.5	0.26	467.81
4.0	148.35	259.6	591.7	592.6	0.46	467.85
5.0	185.44	333.8	924.0	925.4	0.72	467.91
6.0	222.52	408.0	1329.9	1332.0	1.04	467.98
7.0	259.61	482.1	1809.2	1812.0	1.42	468.06
8.0	296.70	556.3	2361.8	2365.5	1.85	468.15
9.0	333.78	630.5	2987.5	2992.3	2.37	468.26
10.0	370.87	704.7	3685.4	3692.2	3.37	468.37
11.0	407.96	778.8	4455.3	4464.2	4.48	468.50
12.0	445.04	853.0	5296.9	5308.3	5.68	468.64
13.0	482.13	927.2	6209.9	6224.1	7.09	468.79
14.0	482.13	964.3	7156.6	7174.2	8.79	468.95
15.0	482.13	964.3	8099.9	8120.8	10.49	469.10
16.0	482.13	964.3	9039.7	9064.1	12.19	469.26
17.0	482.13	964.3	9975.7	10004.0	14.16	469.41
18.0	482.13	964.3	10907.7	10939.9	16.13	469.56
19.0	482.13	964.3	11835.8	11871.9	18.09	469.70
20.0	482.13	964.3	12759.7	12800.0	20.17	469.85
21.0	445.04	927.2	13642.4	13686.9	22.21	469.99
22.0	407.96	853.0	14447.3	14495.4	24.07	470.11
23.0	370.87	778.8	15174.6	15226.1	25.75	470.23
24.0	333.78	704.7	15824.6	15879.3	27.34	470.33
25.0	296.70	630.5	16397.6	16455.1	28.76	470.41
26.0	259.61	556.3	16893.9	16953.9	29.99	470.49
27.0	222.52	482.1	17314.0	17376.0	31.03	470.55
28.0	185.44	408.0	17658.2	17721.9	31.88	470.60
29.0	148.35	333.8	17926.9	17992.0	32.55	470.64
30.0	111.26	259.6	18120.4	18186.5	33.03	470.67
31.0	74.17	185.4	18239.2	18305.9	33.32	470.69
32.0	37.09	111.3	18283.6	18350.5	33.43	470.70
33.0	0.00	37.1	18254.0	18320.7	33.36	470.69

\*\*\*\*\* SUMMARY OF ROUTING COMPUTATIONS \*\*\*\*\*

Pond File: 8169 .PND  
Inflow Hydrograph: 8169-15 .HYD  
Outflow Hydrograph: OUT .HYD

Starting Pond W.S. Elevation = 467.75 ft

\*\*\*\*\* Summary of Peak Outflow and Peak Elevation \*\*\*\*\*

Peak Inflow = 482.13 cfs  
Peak Outflow = 33.43 cfs  
Peak Elevation = 470.70 ft


\*\*\*\*\* Summary of Approximate Peak Storage \*\*\*\*\*

Initial Storage = 0.00 ac-ft  
Peak Storage From Storm = 12.62 ac-ft  
-----  
Total Storage in Pond = 12.62 ac-ft

Pond File: 8169 .PND  
 Inflow Hydrograph: 8169-15 .HYD  
 Outflow Hydrograph: OUT .HYD

EXECUTED: 02-06-1997  
 13:08:23

Peak Inflow = 482.13 cfs  
 Peak Outflow = 33.43 cfs  
 Peak Elevation = 470.70 ft



x File: 8169-15 .HYD Qmax = 33.4 cfs  
 \* File: OUT .HYD Qmax = 482.1 cfs

```

*****
*
*           MANDERLEY ESTATES
*         DETENTION ANALYSIS
*   PREPARED BY: BAX ENGINEERING CO., INC.
*           FEBRUARY 06, 1997
*
*****
  
```

Inflow Hydrograph: 8169-25 .HYD  
 Rating Table file: 8169 .PND

----INITIAL CONDITIONS----  
 Elevation = 467.75 ft  
 Outflow = 0.00 cfs  
 Storage = 0.00 ac-ft

GIVEN POND DATA			INTERMEDIATE ROUTING COMPUTATIONS	
ELEVATION (ft)	OUTFLOW (cfs)	STORAGE (ac-ft)	2S/t (cfs)	2S/t + 0 (cfs)
467.75	0.0	0.000	0.0	0.0
468.25	2.3	2.024	2938.7	2941.0
468.75	6.6	4.092	5941.8	5948.4
469.25	12.1	6.205	9010.2	9022.3
469.75	18.7	8.364	12144.5	12163.2
470.25	26.1	10.573	15351.5	15377.6
470.75	34.3	12.858	18669.1	18703.4
471.25	39.7	15.224	22105.7	22145.4
471.75	61.2	17.674	25663.1	25724.3
472.25	137.4	20.210	29345.2	29482.6
472.75	244.1	22.840	33164.0	33408.1
473.25	374.1	25.567	37123.6	37497.7
473.75	523.5	28.393	41226.5	41750.0
474.25	690.0	31.320	45476.3	46166.3
474.75	872.0	34.354	49881.3	50753.3
475.25	1068.3	37.497	54445.1	55513.4
475.75	1277.9	40.751	59170.7	60448.6

Time increment (t) = 1.0 min.

Pond File: 8169 .PND  
 Inflow Hydrograph: 8169-25 .HYD  
 Outflow Hydrograph: OUT .HYD

INFLOW HYDROGRAPH

ROUTING COMPUTATIONS

TIME (min)	INFLOW (cfs)	I1+I2 (cfs)	2S/t - 0 (cfs)	2S/t + 0 (cfs)	OUTFLOW (cfs)	ELEVATION (ft)
0.0	0.00	-----	0.0	0.0	0.00	467.75
1.0	45.76	45.8	45.7	45.8	0.04	467.76
2.0	91.52	137.3	182.7	183.0	0.14	467.78
3.0	137.28	228.8	410.8	411.5	0.32	467.82
4.0	183.04	320.3	730.0	731.2	0.57	467.87
5.0	228.80	411.8	1140.1	1141.9	0.89	467.94
6.0	274.56	503.4	1640.9	1643.4	1.29	468.03
7.0	320.33	594.9	2232.3	2235.7	1.75	468.13
8.0	366.09	686.4	2914.1	2918.7	2.28	468.25
9.0	411.85	777.9	3685.3	3692.0	3.37	468.37
10.0	457.59	869.4	4545.5	4554.7	4.61	468.52
11.0	503.37	961.0	5494.5	5506.5	5.97	468.68
12.0	549.13	1052.5	6531.7	6547.0	7.67	468.85
13.0	594.90	1144.0	7656.4	7675.7	9.69	469.03
14.0	594.90	1189.8	8822.6	8846.2	11.78	469.22
15.0	594.90	1189.8	9984.0	10012.4	14.18	469.41
16.0	594.90	1189.8	11140.6	11173.8	16.62	469.59
17.0	594.90	1189.8	12292.2	12330.4	19.08	469.78
18.0	594.90	1189.8	13438.5	13482.0	21.74	469.96
19.0	594.90	1189.8	14579.6	14628.3	24.38	470.13
20.0	594.90	1189.8	15715.3	15769.4	27.07	470.31
21.0	549.13	1144.0	16799.8	16859.3	29.75	470.47
22.0	503.37	1052.5	17787.9	17852.3	32.20	470.62
23.0	457.59	961.0	18680.1	18748.8	34.37	470.76
24.0	411.85	869.4	19478.3	19549.5	35.63	470.87
25.0	366.09	777.9	20182.7	20256.2	36.74	470.98
26.0	320.33	686.4	20793.8	20869.2	37.70	471.06
27.0	274.56	594.9	21311.6	21388.7	38.51	471.14
28.0	228.80	503.4	21736.6	21815.0	39.18	471.20
29.0	183.04	411.8	22069.0	22148.5	39.72	471.25
30.0	137.28	320.3	22307.0	22389.4	41.17	471.28
31.0	91.52	228.8	22451.7	22535.8	42.05	471.30
32.0	45.76	137.3	22504.3	22589.0	42.37	471.31
33.0	0.00	45.8	22465.8	22550.0	42.13	471.31

\*\*\*\*\* SUMMARY OF ROUTING COMPUTATIONS \*\*\*\*\*

Pond File: 8169 .PND  
Inflow Hydrograph: 8169-25 .HYD  
Outflow Hydrograph: OUT .HYD

Starting Pond W.S. Elevation = 467.75 ft

\*\*\*\*\* Summary of Peak Outflow and Peak Elevation \*\*\*\*\*

Peak Inflow = 594.90 cfs  
Peak Outflow = 42.37 cfs  
Peak Elevation = 471.31 ft


\*\*\*\*\* Summary of Approximate Peak Storage \*\*\*\*\*

Initial Storage = 0.00 ac-ft  
Peak Storage From Storm = 15.53 ac-ft  
-----  
Total Storage in Pond = 15.53 ac-ft

Pond File: 8169 .PND  
 Inflow Hydrograph: 8169-25 .HYD  
 Outflow Hydrograph: OUT .HYD

EXECUTED: 02-06-1997  
 13:09:06

Peak Inflow = 594.90 cfs  
 Peak Outflow = 42.37 cfs  
 Peak Elevation = 471.31 ft



x File: 8169-25 .HYD Qmax = 42.4 cfs  
 \* File: OUT .HYD Qmax = 594.9 cfs